



# Ar-ChemAG

# CONCRETE PAD & DIKE SEALER

## EPOXY ESTER SEAL

Protects against staining from Prowl®, Treflan®, & other pesticides.  
Impervious to acids, fertilizers, pesticides & other agricultural chemicals.  
One gallon covers 300-500 square feet.

### DANGER

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes eye irritation. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

**KEEP OUT OF REACH OF CHILDREN**

NET CONTENTS:  1  5  20  35  55 Gallon(s)

# CONCRETE PAD & DIKE SEALER



PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com



### DANGER:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes eye irritation. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

### PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground bond container and receiving equipment. Use explosion-proof lighting, electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist, spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **If skin irritation or rash occurs:** Get medical advice/attention.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**If eye irritation persists:** Get medical advice/attention. **If exposed or concerned:** Get medical advice/attention. Get medical advice/attention if you feel unwell.

**In case of fire:** Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

### NFPA® RATINGS:

Health: 3; Flammability: 2; Reactivity: 0



Please Recycle.

While concrete is a durable surface, it still needs protection from water damage and heavy usage. Give your floors the superior finish they deserve with **AR-CHEM AG CONCRETE PAD & DIKE SEALER** from Share. An exceptional blend of epoxy ester resins gives your concrete floors a durable finish that resists weather, wear and tear and the barrage of harmful substances that frequently fall or spill. When **AR-CHEM AG CONCRETE PAD & DIKE SEALER** is properly applied, concrete floors become smoother and make the removal of dirt easier when sweeping and scrubbing. For a durable, resilient concrete floor, use the durable, resilient finish from Share -- **AR-CHEM AG CONCRETE PAD & DIKE SEALER**.

### DIRECTIONS FOR USE:

New concrete must be cured a minimum of 90 days prior to sealing. To remove dirt, oil, and other surface contaminants, clean the surface with a solution of **AR-CHEM AG HEAVY DUTY FLOATER CLEANER**. Allow the surface to dry thoroughly. To prepare the surface to accept the sealer, etch using **AR-CHEM AG PAD CLEANER & ETCH** according to the label directions. Flush surface with water and allow to dry completely. Apply the first coat of seal to dry concrete with lamb's wool applicator. Allow the first coat to dry 4 to 6 hours depending upon temperature and humidity then apply second coat for a smooth impervious surface. Concrete is traffic ready in 24 hours.

### WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

### INGREDIENTS/CAS #:

Distillates (Petroleum), Hydrotreated Light (64742-47-8); Proprietary Epoxy Resin (Mixture); Medium Aliphatic Solvent Naphtha (Petroleum) (64742-88-7); Mixed Xylenes (1330-20-7); Ethyl Benzene (100-41-4); Cumene (98-82-8)

Dispose of contents/container to comply with local/regional/national/international regulations.

0124.050615