



# INHIBITED WATER METER CLEANER

**INHIBITED ACID CLEANER**  
DISSOLVES RUST-LIME-SCALE-MINERAL DEPOSITS

## DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.  
May cause respiratory irritation.

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS: ■ 1 ■ 5 ■ 20 ■ 35 ■ 55 Gallon(s)**

# INHIBITED WATER METER CLEANER



**PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com**



Keep only in original container. Do not breathe mist, spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

**IF SWALLOWED:** rinse mouth. Do NOT induce vomiting.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER. Call a doctor, a POISON CENTER if you feel unwell.

Absorb spillage to prevent material damage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

*For industrial and commercial use only.  
For additional information, see Safety Data Sheet.*

### WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

**INHIBITED WATER METER CLEANER** dissolves rust, lime, and minerals on surfaces such as machinery parts, water meters, and cement trucks. Cleans boilers, cooling systems, old and new masonry, and radiators. Removes cement and excess mortar from tools, brickworks, etc.

### DIRECTIONS

To clean and descale water meters and metal parts, submerge parts in undiluted **INHIBITED WATER METER CLEANER** and soak until all deposits are dissolved. Rinse thoroughly with clean water. For light deposits, dilute **INHIBITED WATER METER CLEANER** with 3 to 5 parts water. To descale boilers, cooling towers, condensers, heat exchangers, and other water handling systems, dilute **INHIBITED WATER METER CLEANER** with 8 to 10 parts water. Allow solution to soak or circulate in system for 4 to 8 hours, until scale is removed. Flush system thoroughly with clean water.

### NFPA® Ratings

Health: 3; Flammability: 0; Reactivity: 0

### Contains/CAS Number:

Water/7732-18-5; Hydrochloric Acid/7647-01-0; Surfactant/Proprietary; Tallow Alkyldiamine Ethoxylate/61790-85-0; Acid Blue 93/28983-56-4

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0140.050115