



READY-TO-USE

DEVOUR

CONCRETE REMOVER & DISSOLVER



BIODEGRADABLE FORMULA

**EASY-TO-USE FOR FAST REMOVAL AND
CLEAN UP OF CONCRETE ON MOST SURFACES**

DANGER

May be corrosive to metals. Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage.

KEEP OUT OF REACH OF CHILDREN

Net Contents: □ 1 □ 5 □ 20 □ 35 □ 55 Gallons

DEVOUR

CONCRETE REMOVER & DISSOLVER



**PO BOX 245013
MILWAUKEE, WI 53224**

800.776.7192

www.sharecorp.com

USE ON:

**HAND TOOLS
SCREEDS
MOLDS
SAWS
CHUTES
FORMS**

**CONCRETE MIXERS
TROWELS
RAKES & SHOVELS
CEMENT TRUCKS
VEHICLES
WHEELBARROWS**

**NO MORE HAMMERING, SCRAPING
OR SAND BLASTING!**



DANGER: May be corrosive to metals. Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage.

Keep only in original packaging. Avoid breathing mist, spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective clothing, eye and face protection.

IF SWALLOWED: Call a poison center or doctor if you feel unwell. Rinse mouth.

IF ON SKIN: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.

Absorb spillage to prevent material damage.

Dispose of contents and/or container to comply with local/regional/national/international regulations.



WARNING: This product can expose you to 1,4-Dioxane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

DIRECTIONS:

PREPARATION:

DEVOUR is ready-to use and is most effective on dry, hard concrete. Make sure to protect surrounding surfaces in the area that **DEVOUR** is being used. Remove any loose concrete with a brush or blower prior to using **DEVOUR** as this will speed up the process.

APPLICATION: Spray • Brush On • Soak

DEVOUR should **NOT** be applied on to a **HOT SURFACE**. It will evaporate too quickly and could possibly damage the surface being cleaned. Pour, soak, spray, or brush **DEVOUR** on to the hardened and dry concrete to be removed. The product will begin to have a small amount of foam while it begins to work. The foaming will begin reducing fairly quickly. Allow **DEVOUR** to continue working for at least 30 minutes or until the concrete becomes soft. For **HEAVY BUILDUPS** allow **DEVOUR** to work for 12 hours and then re-apply to soften up the concrete further. Once the concrete is softened, remove the dissolved concrete with a pressure washer, hose, or brush if necessary. Should there still be concrete remaining, re-apply as necessary.

NOTE: DEVOUR will not remove paint. Paint may sometimes come off on rusted surfaces where brushing or pressure washing will remove rusted particles that are painted.

NFPA® Ratings

Health: 2; Flammability: 1; Reactivity: 0

Contains/CAS Number:

Water (7732-18-5); Urea Hydrochloride (506-89-8); C7-21 Alcohols Ethoxylated (68991-48-0); Propylene Glycol Butyl Ether (5131-66-8); Hydroxyphosphonoacetic Acid (23783-26-8).

For industrial and commercial use only.

For additional information, see Safety Data Sheet



Please Recycle.

0149.072026