

DEVOUR

Concrete Remover & Dissolver

Form: Liquid

Color: Yellow

Odor: Mild

pH: 0 - 2

Specific Gravity: 1.07

Density: 9.02 lb/gal

Storage Stability (at 70°F): 1 year

This Product Contains:	CAS#
Water	7732-18-5
Urea Hydrochloride	506-89-8
C7-21 Alcohols Ethoxylated	68991-48-0
Propylene Glycol Butyl Ether	5131-66-8
Hydroxyphosphonoacetic Acid	23783-26-8

Great For Use On...

- Hand tools
- Screeds
- Molds
- Saws
- Chutes
- Forms
- Concrete mixers

APPLICATION:

Spray • Brush On • Soak

DEVOUR should NOT be applied to a HOT SURFACE. It will evaporate too quickly and could possibly damage the surface being cleaned. Pour, soak, spray, or brush **DEVOUR** on to the hardened and dry concrete to be removed. The product will begin to have a small amount of foam while it begins to work. The foaming will begin reducing fairly quickly. Allow **DEVOUR** to continue working for at least 30 minutes or until the concrete becomes soft. For HEAVY BUILDUPS allow **DEVOUR** to work for 12 hours and then re-apply to soften up the concrete further. Once the concrete is softened, remove the dissolved concrete with a pressure washer, hose, or brush if necessary. Should there still be concrete remaining, re-apply as necessary.

CONSULT PRODUCT LABEL FOR DETAILED DIRECTIONS

HMIS			NFPA®		
	Severe	4	Extreme		
Health.....2	Serious	3	High	Health.....2	
Flammability.....1	Moderate	2	Moderate	Flammability.....1	
Reactivity.....0	Slight	1	Slight	Reactivity.....0	
Personal Protection.....X	Minimal	0	Insignificant	Special Precautions.....None	