



TRIDENT

WATER TREATMENT

TOWERGUARD ANTI-FOAM

CONCENTRATED DEFOAMER

CONTROLS FOAM CAUSED BY HIGH ALKALINITY AND SOLIDS

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)



TOWERGUARD ANTI-FOAM



P.O. Box 245013

Milwaukee, WI 53224

(800) 776-7192

www.sharecorp.com



TOWERGUARD ANTI-FOAM

Disposal:

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

NFPA® Ratings

Health: 0; Flammability: 0; Reactivity: 0

Contains/CAS Number:

Water/7732-18-5; Polydimethylsiloxane/63148-62-9; Proprietary/Mixture; 2,2',2'-nitrioltris-ethanol/102-71-6; DMDM Hydantoin/Mixture



Please Recycle.

The non-polluting, water-based formulation of **TRIDENT TOWERGUARD ANTI-FOAM** contains special silicone defoaming agents for fast knock-down of foam due to high levels of organic materials in the tower, turbulence and even descaling operations.

DIRECTIONS

If possible, meter **TRIDENT TOWERGUARD ANTI-FOAM** into cooling tower prior to foaming problem. If not possible to meter into system prior to foaming problem, apply **TRIDENT TOWERGUARD ANTI-FOAM** into the cooling tower's sump.

Normal application rates range from 50 to 100 ppm (1/2 gallon to 1 gallon per 10,000 gallons of cooling tower capacity). The amount of **TRIDENT TOWERGUARD ANTI-FOAM** used will vary depending upon environmental and water conditions.

When descaling a cooling tower, larger concentrations of **TRIDENT TOWERGUARD ANTI-FOAM** will have to be used.

0365.050715