



# Ar-ChemAG

# Slick Shot

Prevents pesticides, fertilizers and adjuvant residues from adhering.  
Easily applied with hand sprayer, paint roller or brush.

## DANGER

Flammable liquid and vapour. May be fatal if swallowed and enters airways.  
May cause an allergic skin reaction. Suspected of causing cancer.

**KEEP OUT OF REACH OF CHILDREN**

NET CONTENTS:  1  5  20  35  55 Gallon(s)

# Ar-ChemAG

# Slick Shot



PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com



### DANGER:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Suspected of causing cancer.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, spray. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**If skin irritation or rash occurs:** Get medical advice/attention.

**If exposed or concerned:** Get medical advice/attention.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

**In case of fire:** Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

Keep equipment looking new with **AR-CHEM AG SLICK SHOT** from Share. Chemical additives have been incorporated to protect surfaces from nicks, scratches and scrapes. **AR-CHEM AG SLICK SHOT** also serves two other important functions - it provides a high gloss to all painted and plated metal surfaces and it creates a slick surface that keeps unwanted deposits from adhering to equipment making clean up quick and easy.

### DIRECTIONS:

Apply with a sprayer, paint roller or brush. For best results and longer life, wash the vehicle with **HEAVY DUTY FLOATER CLEANER**, rinse and allow to dry before applying **AR-CHEM AG SLICK SHOT**.

Two light coats, allowing an hour of drying time between applications, will provide good protection and will prevent unwanted deposits from adhering to equipment surfaces, allowing for faster and easier equipment clean-up.

### INGREDIENTS/CAS #:

Distillates (Petroleum), Hydrotreated Light (64742-47-8); Polydimethylsilicone (63148-62-9); Mixed Xylenes (1330-20-7); Cumene (98-82-8); Fragrance (Mixture)

### NFPA® RATINGS:

Health: 2; Flammability: 2; Reactivity: 0

**WARNING:** This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

0386.052015