



Siliconized EQUIPMENT COATING

GENERAL PURPOSE RELEASE AGENT

PROTECTS AS IT REDUCES FRICTION FOR MORE EFFICIENT OPERATION

DANGER

Flammable liquid and vapour. May be fatal if swallowed and enters airways.
May cause an allergic skin reaction. Suspected of causing cancer.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

Siliconized EQUIPMENT COATING



**PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com**



DANGER:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Suspected of causing cancer.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, spray. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

NFPA® RATINGS:

Health: 2; Flammability: 2; Reactivity: 0



Please Recycle.

Keep equipment looking new with **SILICONIZED EQUIPMENT COATING** from Share. Chemical additives have been incorporated to protect surfaces from corrosion, nicks, scratches and scrapes. **SILICONIZED EQUIPMENT COATING** also serves two other important functions - it provides a high gloss to all painted and plated metal surfaces and it creates a slick surface that keeps unwanted deposits from adhering to equipment making clean up quick and easy.

DIRECTIONS:

Apply with a sprayer, paint roller or brush. For best results and longer life, wash equipment thoroughly and allow to dry before applying **SILICONIZED EQUIPMENT COATING**. Two light coats, allowing one hour of drying time between applications, will provide good protection and prevent unwanted deposits from bonding to the surface.

For maximum protection, apply **SILICONIZED EQUIPMENT COATING** at the end of each work period. Several applications over summer storage periods will preserve equipment.

SILICONIZED EQUIPMENT COATING is ideal for use on shovels, loaders, snow throwers and truck beds to allow easier, more complete dumping.

INGREDIENTS/CAS #:

Distillates (Petroleum), Hydrotreated Light (64742-47-8); Polydimethylsilicone (63148-62-9); Mixed Xylenes (1330-20-7); Cumene (98-82-8); Fragrance (Mixture)

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity. 0386.052015