



SILICONIZED SNOW PLOW COATING

PROTECTS AS IT REDUCES FRICTION FOR MORE EFFICIENT PLOWING

DANGER

Flammable liquid and vapour. May be fatal if swallowed and enters airways.
May cause an allergic skin reaction. Suspected of causing cancer.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

SILICONIZED SNOW PLOW COATING

SPECIMEN LABEL



**PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com**



DANGER:
Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Suspected of causing cancer.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, spray. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.
IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If skin irritation or rash occurs: Get medical advice/attention.
If exposed or concerned: Get medical advice/attention.

In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.



SILICONIZED SNOW PLOW COATING covers plow blades and snow removal equipment with a hard, slippery layer of silicone. Snow slides off treated surfaces easier and faster, allowing more snow to be removed with less fuel and less wear on equipment.

DIRECTIONS:
Apply **SILICONIZED SNOW PLOW COATING** to plow blades and other exposed metal surfaces by spraying, brushing, swabbing or rolling. Equipment may be used immediately after application, but best results are obtained when coating is allowed to dry for 20-40 minutes.

For maximum protection, apply **SILICONIZED SNOW PLOW COATING** at the end of each work period. Several applications over summer storage periods will help protect equipment while in storage.

SILICONIZED SNOW PLOW COATING is ideal for use on shovels, loaders, snow throwers and truck beds to help prevent corrosion and allow easier, more complete dumping.

NFPA® RATINGS:
Health: 2; Flammability: 2; Reactivity: 0

INGREDIENTS/CAS #:
Distillates (Petroleum), Hydrotreated Light (64742-47-8); Polydimethylsilicone (63148-62-9); Mixed Xylenes (1330-20-7); Cumene (98-82-8); Fragrance (Mixture)

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

0386.052015