



# GOOD ORANGE

## FLOATING LIFT STATION SOLVENT DEGREASER

DISSOLVES & LOOSENS FATS AND GREASE  
FROM LIFT STATIONS AND SEWER LINES

### DANGER

Combustible Liquid. May be fatal if swallowed and enters airways.

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS:**  1  5  20  35  55 Gallon(s)

# GOOD ORANGE



**PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com**

# GOOD ORANGE



### DANGER:

Combustible Liquid. May be fatal if swallowed and enters airways.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear eye protection, protective clothing, protective gloves.

**IF SWALLOWED:** Immediately call a poison center or doctor. Do NOT induce vomiting.

**In case of fire:** Use extinguishing powder, foam to extinguish. Store in a well-ventilated place. Store locked up.

### DISPOSAL:

Dispose of contents and container to comply with local/regional/national/international regulations.

*For Industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*



**PO BOX 245013 • MILWAUKEE, WI 53224 • 800.776.7192 • www.sharecorp.com**

- Economical with a usage rate of 1/2 gallon per square foot of water surface.
- Use in sewer lines, lift stations and grease traps.
- Formulated with a pleasant orange fragrance.
- Color indicator provides easy visual verification of the proper product level in lift stations.
- A VOC compliant degreaser and deodorant.

**GOOD ORANGE** Floating Lift Station Solvent Degreaser is a pleasantly scented solvent degreaser specially formulated to dissolve grease and fats in sewer lines, lift stations and grease traps. This product floats on the surface of the water to strip away fat and grease accumulations as water levels naturally rise and fall. Built-in emulsifiers entrap the debris and dissolved greases in the solvent to aid in complete removal. A built-in, color level indicator allows the operator to determine product level by visual inspection.

### DIRECTIONS:

Use 1/2 gallon of **GOOD ORANGE** Floating Lift Station Degreaser per square foot of water surface. Apply when the lift station is at its lowest level by spraying or pouring directly down the lift station walls. It is recommended to maintain a 1-to-2-inch layer of **GOOD ORANGE** Floating Lift Station Degreaser on the surface at all times.

### NFPA® RATINGS

Health: 1; Flammability: 1; Reactivity: 0

### INGREDIENTS/CAS #:

Hydrotreated Light Alkanes (64742-47-8); Propylene Carbonate (108-32-7); Undeceth-5 (34398-01-1); Undecanol (112-42-5); Solvent Orange 7 (3118-97-6).



Please Recycle.

0496.111925