



SEWER Compound XX

NON-FLAMMABLE FUMES • FAST ACTING • EFFECTIVE • EFFICIENT

DANGER:

May intensify fire; oxidizer. Causes severe skin burns and eye damage. May cause respiratory irritation.

See additional cautions on side panel.

KEEP OUT OF REACH OF CHILDREN

Net Contents: 55 Pounds



**READ ENTIRE LABEL CAREFULLY BEFORE USING.
FOR USE BY TRAINED PERSONNEL ONLY.
NOT FOR RETAIL SALE OR HOUSEHOLD USE.**

This drain opener contains powerful caustic granules activated with aluminum needles. When added to water in a drain or sewer, it releases large amounts of heat and turbulence to liquefy, dissolve and loosen animal and vegetable fats and oils, hair, paper, organic matter and other materials that clog drains and sewer lines.

Keep away from open flames. No smoking. Keep/Store away from clothing, combustible materials. Take any precaution to avoid mixing with acids, reducing agents, water. Product will generate large amounts of heat when wetted. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Do not breathe dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a doctor, POISON CENTER if you feel unwell.

In case of fire: Use foam, dry extinguishing powder, carbon dioxide (CO2) to extinguish.

Dispose of contents/container to comply with local/regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

SEWER COMPOUND XX is specially formulated to generate maximum heat and turbulence rapidly upon contact with water. It will liquefy, emulsify, dissolve and loosen animal and vegetable fats and oils, hair, paper, organic matter and many other materials that tend to clog drains and sewer lines. It will not injure pipes, drains, or sewer lines. **SEWER COMPOUND XX** is specifically formulated to reduce the release of flammable gases or vapors when used according to directions to remove normal sewer and drain obstructions. **AVOID SMOKING WHEN USING SEWER COMPOUND XX COMPOUND. DO NOT THROW LIGHTED CIGARETTES OR MATCHES INTO MANHOLES WHILE TREATING. SEWER COMPOUND XX** also contains a blend of highly visible tracing dyes for observing the effects of the use of the product.

DIRECTIONS: For Municipal Use - Pour or shovel about 25 pounds of **SEWER COMPOUND XX** into manholes upstream and closest to the obstruction. A second addition following the first by 0-15 minutes may be necessary to remove more difficult obstructions. For a completely plugged drain or sewer having a large volume of water, add **DYNASTY 300 EC** to the drain or sewer and allow the enzymes to act for at least 12 hours before adding **SEWER COMPOUND XX**. In practically all cases, the enzymes will liquefy enough of the obstruction so that a partial flow is obtained. Then the effects of **SEWER COMPOUND XX** will not be diluted by excessive amounts of water.

For Industrial Use - Use 1 or 2 pounds of **SEWER COMPOUND XX** in normal drains. In food plants (such as packing houses, processing plants, and canneries where accumulations of organic matter are particularly high) 10 to 20 pounds may be required.

Always remove as much standing water in manholes, catch basins, and sewers as possible before adding **SEWER COMPOUND XX**. Add product **SLOWLY** and carefully. **NEVER USE A PLUNGER WITH THIS PRODUCT. NEVER USE HOT WATER. USE OF SEWER COMPOUND XX GENERATES CONSIDERABLE HEAT WHICH MAY CAUSE ERUPTION OF DRAIN CONTENTS. IF POSSIBLE, PLACE A BUCKET OR OTHER DEEP CONTAINER OVER DRAIN OPENING AFTER TREATING. NEVER LOOK INTO DRAIN AFTER TREATING.** Do not use in combination with or directly after treatment with acid type drain openers - **SEWER COMPOUND XX** will react violently or explosively with acid drain opener products. Do not enter treated sewers until they have been thoroughly flushed with water.

NFPA* Ratings:

Health: 3; Flammability: 0; Reactivity: 2 Special: W

Contains/CAS Number:

Sodium Hydroxide/1310-73-2; Sodium Nitrate/7631-99-4;
Sodium Chloride/7647-14-5; Aluminum Metal/7429-90-5; Dye/Mixture



Please Recycle.