



GAS LINE ANTI-FREEZE GASOLINE ADDITIVE

FUEL LINE ANTI-FREEZE AND DE-ICER
PREVENTS FROZEN FUEL LINES & CARBURETOR ICING.

DANGER

Highly flammable liquid and vapour. Toxic if swallowed or in contact with skin. Fatal if inhaled. Causes damage to organs.

KEEP OUT OF REACH OF CHILDREN

Net Contents: 1 □ 5 □ 20 □ 35 □ 55 □ Gallons

GAS LINE ANTI-FREEZE GASOLINE ADDITIVE



P.O. Box 245013
Milwaukee, WI 53224
800.776.7192
www.sharecorp.com



DANGER:

Highly flammable liquid and vapour. Toxic if swallowed or in contact with skin. Fatal if inhaled. Causes damage to organs.

PREVENTION:

Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist, spray, vapours. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. In case of inadequate ventilation wear respiratory protection.

IF SWALLOWED: Rinse mouth. Immediately call a doctor, a POISON CENTER.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If exposed: Call a poison center/doctor. Immediately call a doctor, a POISON CENTER.

In case of fire: Use alcohol resistant foam, dry extinguishing powder, carbon dioxide (CO2) to extinguish.

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/international regulations.

GAS LINE ANTI-FREEZE GASOLINE ADDITIVE

GAS LINE ANTI-FREEZE is specially formulated for gasoline engines to prevent frozen fuel lines and carburetor icing. It promotes easier and faster starting. Regular use will free sticky valves, reduce or eliminate carbon formation, and keep the fuel system clean and free from moisture.

DIRECTIONS:

For winter protection, add **GAS LINE ANTI-FREEZE** at the rate of 12 ounces per 10-20 gallons of fuel. For regular preventive maintenance, add 12 ounces per 25-30 gallons of fuel.

NFPA® RATINGS

Health: 2; Flammability: 3; Reactivity: 0

INGREDIENTS/CAS #:

Methanol (67-56-1)

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.



Please Recycle.

0650.060515