

FUEL OIL ANTI-GEL

Low Temperature Fuel Oil Additive

Form: Liquid

Color: Colorless

Odor: Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): N/D

Flash Point (ASTM D-7821): 120 °F

Specific Gravity: 0.89 g/cm³

Density: 7.43 lbs/gal

Storage Stability (at 70°F): 1 year

Excellent for use by...

- **Rail Fleet Operators**
- **Service Stations**
- **Fuel Oil Dealers**
- **Fuel Oil Haulers**
- **Boiler Operators**
- **Truck Fleet Operators**

Ingredients

C.A.S. #

Light aromatic solvent naphtha.....64742-95-6
 Solvent naphtha (Petroleum),
 Heavy aromatic.....64742-94-5
 1, 2, 4 - Trimethylbenzene95-63-6
 Naphthalene91-20-3
 Vinyl acetate.....108-05-4

DIRECTIONS: Add 12 ounces of FUEL OIL ANTI-GEL to 150 gallons of fuel or 1 gallon to 1500 gallons of fuel.

This dosage will lower the pour point of most residual fuels by about 20 °F. In some cases, additional treatment will lower the pour point by several more degrees. For best results, fuels should be at 10 °F above the normal pour point when FUEL OIL ANTI-GEL is blended in.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	2
Flammability.....	Moderate	2	Moderate	Flammability.....	2
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None