

TRIDENT TOWER CLOUT

Cooling Tower Cleaner and Organic Foulant Remover

Form: Powder

Color: White

Odor: Odorless

pH: N/D

Solubility (in water): Soluble
(in mineral spirits): N/D

Viscosity (CPS at 70°F): N/A

Flash Point (ASTM D-7821): N/A

Specific Gravity: 0.8 – 1.2 g/cm³

Density: 6.68 – 10.01 lbs/gal

Storage Stability (at 70°F): 1 year

Assists with removal of...

- **Biomass**
- **Algae**
- **Organic Matter**
- **Biofilms**

<u>Ingredients</u>	<u>C.A.S. #</u>
Sodium Percarbonate	15630-89-4
Sodium Carbonate	497-19-8
Sodium Metasilicate.....	6834-92-0

Treatment feed rates will vary depending upon the severity of the fouling. For maintenance of clean surfaces in previously cleaned systems, this product should be fed at a rate of 6 to 8 oz. 1-3 days per week in slug dosages. Feed at a rate of 12 - 16 oz. 2 or 3 times per week for systems that have greater tendencies to foul due to biomass or organically bound contamination. Heavily fouled systems may tend to dislodge large amounts of material deposits. Precautions should be taken to prevent plugging of screens, small lines and heat exchangers.

NOTE: Do not leave a diluted solution of TRIDENT TOWER CLOUT in a sealed container for a long time. The solution continues to give off oxygen causing the container to leak. Do not use on silk, wool or leather. Do not mix with bleach.

HMIS®			NFPA®		
	Severe	4	Extreme		
Health	Serious	3	High	Health	2
Flammability	Moderate	2	Moderate	Flammability.....	0
Reactivity	Slight	1	Slight	Reactivity.....	1
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	OX