



PO BOX 245013 **MILWAUKEE, WI 53224** 800.776.7192 www.sharecorp.com



### DANGER:

May be corrosive to metals. Harmful if swallowed. Causes severe skin burns and eve damage.

#### PREVENTION:

Keep only in original container. Do not breathe mist, spray. Wash thoroughly aften handling. Do not eat, drink or smoke when using this product. Wear eve protection, protective dothing, protective gloves.

IF SWALLOWED: Rinse mouth. Do NOT Induce

IF ON SKIN (OR HAJR). Take off immediately all contaminated clothing. Rinse skin with water/shower if inhaled. Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

## STORAGE:

Store locked up. Store in corrosive resistant container with a resistant inner liner.

## DISPOSAL:

Dispose of contents/container to comply with local/regional/national/international regulations. MILDEW STAIN REMOVER is a powerful concentrate formulated to remove mildew stains and mildew odor on many surfaces. It works quickly and efficiently on bathroom tile, grout, plastic and fiberglass shower stalls, vinyl mats and awnings. It is ideal for use on painted surfaces before repainting.

### **DIRECTIONS:**

Dilute **MILDEW STAIN REMOVER** with warm or cold water. Use 1 part of **MILDEW STAIN REMOVER** diluted with 8 to 10 parts water when extreme cleaning power is required. Use dilutions of up to 1:50 for lighter cleaning chores. Dilution ratios may be adjusted to give the desired results and speed of cleaning. MILDEW **STAIN REMOVER** will produce clinging foam when applied with foam generating equipment.

NOTE: Rinse surfaces immediately after use if MILDEW STAIN REMOVER is used on vinyl, plastic or rubber. MILDEW STAIN REMOVER is not for use on fabric or painted surfaces unless they are to be repainted. Avoid prolonged contact with metal, wood, or porcelain as damage may occur.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

# NFPA® RATINGS:

Health: 2; Flammability: 0; Reactivity: 1

## **INGREDIENTS/CAS #:**

Water (7732-18-5); Potassium Hydroxide (1310-58-3); Sodium Tripolyphosphate (7758-29-4); Sodium Hypochlorite (7681-52-9); Lauramine Oxide (1643-20-5).



0690.040115