

# The Oxynator

## Professional Strength Drain Opener

**Form:** Liquid

**Color:** Clear, colorless liquid

**Odor:** Pungent

**pH:** N/D

**Solubility (in water):** Soluble  
**(in mineral spirits):** Insoluble

**Flash Point (ASTM D-7821):** N/D

**VOC Content (% by weight):** 0%

**Specific Gravity:** 1.05 g/cm<sup>3</sup>

**Density:** 8.76 lbs/gal

**Shelf Life (at 70°F):** 6 months unopened

<u>Ingredients</u>	<u>C.A.S. #</u>
Water.....	7732-18-5
Hydrogen Peroxide .....	7722-84-1

<b>Eliminates...</b>
<ul style="list-style-type: none"> <li>• <b>Grease</b></li> <li>• <b>Oil</b></li> <li>• <b>Fats</b></li> <li>• <b>Odors</b></li> <li>• <b>Most Organic Matter</b></li> </ul>

**DIRECTIONS: GREASE TRAPS & DRAIN LINES:** Use THE OXYNATOR for cleaning out and removing heavy grease accumulations from grease traps and drains. Pour approximately one to three gallons of THE OXYNATOR carefully into each drain opening as close to the grease trap as possible. Next, treat drains further away from the grease trap. NOTE: Foam may generate and come up through floor drains. Foam can be rinsed back into the drain with water. If necessary, cold water can be added to slow down the cleaning process.

<b>HMIS®</b>			<b>NFPA®</b>		
	Severe	4	Extreme		
Health .....	Serious	3	High	Health.....	2
Flammability.....	Moderate	2	Moderate	Flammability.....	0
Reactivity.....	Slight	1	Slight	Reactivity.....	1
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	OX