



ORGANIC

WATER SYSTEM CLEANER

WATER CLARIFIER

DANGER

Causes serious eye irritation. Suspected of causing cancer. Causes damage to organs. May cause damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

SPECIMEN LABEL

ORGANIC

WATER SYSTEM CLEANER



PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com



DANGER: Causes serious eye irritation. Suspected of causing cancer. Causes damage to organs. May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray, vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, protective clothing, protective gloves.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. **If exposed or concerned:** Get medical advice/attention. Get medical advice/attention if you feel unwell.

Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

INGREDIENTS/CAS #:

Water (7732-18-5); Anionic Polyacrylamide (Proprietary); Tetrasodium Ethylenediamine Tetraacetate (64-02-8); Ethylene Glycol (107-21-1); Triethanolamine (102-71-6).

ORGANIC WATER SYSTEMS CLEANER is a water-based, non-solvent formulation which is effective in cleaning water cooling systems and swimming or ornamental pools in several ways.

1. Coagulates suspended matter and clears water.
2. Cleans filters, screens, pipelines and valves of scale and slime.
3. Controls biological malodors.
4. Loosens scum, slime, scale, rust and dirt. Prevents more from adhering.
5. Provides faster, full flow filtration with cleaner filtrates, and easier cleaning of filter systems.
6. Increases capacity of radiators and heat exchangers.
7. Compatible with chemicals commonly used in cooling systems and swimming pools.

DIRECTIONS:

Use 1 pint to 1/2 gallon per day per 10,000 gallons of system or pool water (10-55 ppm). This dosage may be reduced with continued use and depending upon the severity of the problem. When scale and slime are under control, applications once or twice a week may be sufficient.

WARNING: This product can expose you to acrylamide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0



Please Recycle.

1233.050918