

HYDRANT ANTI-FREEZE

Non-Hazardous Anti-Freeze



Form: Liquid

Color: Clear, Colorless

Odor: No odor

pH: 7

Solubility (in water): Soluble
(in mineral spirits): No data available

VOC Content (% by weight): 0

Flash Point (Closed Cup): 228.2°F

Specific Gravity: 1.04 g/cm³

Density: 8.68 lbs/gal

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
1,2-Propanediol.....	57-55-6

Other Uses...	
<ul style="list-style-type: none"> • Cooling tower anti-freeze • Chilled loop anti-freeze • Radiators • Water cooled engines • The food transportation industry will enjoy using HYDRANT ANTI-FREEZE where an undetected spill or leak may contaminate food. 	

DIRECTIONS: Drain as much water as possible from hydrant. Fill hydrant with HYDRANT ANTI-FREEZE, leaving air space below cover to allow liquid to expand and contract with changing temperatures. HYDRANT ANTI-FREEZE is a food grade material that will not contaminate potable water supplies, but treated hydrants should be rinsed thoroughly before the water is used for domestic purposes.

Undiluted: HYDRANT ANTI-FREEZE will protect hydrants down to -60°F.

Diluted: Use of a 1:1 dilution ratio with water and HYDRANT ANTI-FREEZE will protect down to -25°F.

HMIS®			NFPA®		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	0
Flammability.....	Moderate	2	Moderate	Flammability	1
Reactivity.....	Slight	1	Slight	Reactivity	0
Personal Protection	Minimal	0	Insignificant	Special Precautions	None