# BIODEGRADABLE WATER WETTING AGENT

CORP

Increases effectiveness & coverage quickly penetrates cotton, upholistery, wood, paper, grass and brush fires.

## DANGER

Harmful if swallowed. Causes serious eye damage. Suspected of causing cancer.

KEEP OUT OF REACH OF CHILDREN NET CONTENTS: 1 1 5 20 35 55 Gallon(s)



PO BOX 245013 MILWAUKEE, WI 53224 800.776.7192 www.sharecorp.com



**DANGER:** Harmful if swallowed. Causes serious eye damage. Suspected of causing capper.

PRECAUTIONS Obtain special instructions before use. Do not handle until all safety precautions have been read and understood Wash thorpughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, protective clothing, protective gloves.

F SWALLOWED: Rinsonnouth. Call a doctor, a POISON

**IF INTYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/ attention. Immediately call a doctor, a POISON CENTER

Store locked up.

#### DISPOSAL:

Dispose of contents/container to comply with local/ regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

#### WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

#### 500 GALLONS OF WATER CONTAINING FIREMAN'S AID IS MORE EFFECTIVE THAN 1500 GALLONS OF UNTREATED WATER

FIREMAN'S AID is formulated to increase the wetting efficiency of water used for fire fighting. It is especially effective in extinguishing stubborn blazes which have a tendency to smolder, such as brush fires, clothing, bedding, rags, upholstery, etc. This formulation is non-corrosive, lubricates packings, and will not harm storage tanks, nozzles, couplings, etc. FIREMAN'S AID is compatible with Share's TANK PROTECTOR so that both can be used in the same tank for increased effectiveness and longer tank life.

## DIRECTIONS:

Add 1/2 to 1 gallon of **FIREMAN'S AID** per 100 gallons of water, using the larger amount with increasing water hardness. To produce or stabilize foam, use 1 to 2 gallons of **FIREMAN'S AID** per 100 gallons of water. The amount of **FIREMAN'S AID** to be used per 100 gallons of water will vary with the quality of foam desired, and the water hardness.

## **NFPA<sup>®</sup> RATINGS**

Health: 2; Flammability: 0; Reactivity: 0

## INGREDIENTS/CAS #:

Water/7732-18-5; Nonylphenol Polyethoxylate/ 9016-45-9; Cocoamide/8051-30-7; Coco Soaps/ 7487-79-8; Diethanolamine/111-42-2



