



OIL & GREASE

Eliminator

**BIODEGRADABLE FORMULA
EMULSIFIES AND DISPERSES OIL, GREASE, GASOLINE & SOLVENTS**

DANGER:
Causes serious eye damage.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

OIL & GREASE

Eliminator



**PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com**



DANGER:

Causes serious eye damage.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NFPA® RATINGS

Health: 0; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water (7732-18-5); Undeceth-5 (34398-01-1); Sodium Xylene Sulphonate (1300-72-7); Glycerin (56-81-5); Sodium Sulfate (7757-82-6).

DIRECTIONS:

For gasoline, solvent, or fuel spills, apply **OIL AND GREASE ELIMINATOR** full strength or diluted 1:1 with water. Allow to penetrate spill and hose off with water under pressure. Cleanups need to be contained then picked-up and disposed of properly. Fire hazard is greatly reduced or eliminated after fuel is emulsified.

For oil slicks, apply sufficient quantity to begin the break up of the slick. Agitate mechanically, if possible, mix the oil with the water base.


To remove slicks from larger water areas, spray or drip **OIL AND GREASE ELIMINATOR** full strength on the oil at low tide, and natural tide action will cleanse the sand.

In sewage treatment plants, apply **OIL AND GREASE ELIMINATOR** full strength on oil and grease to solubilize. Quantity to be applied will depend upon the amount of oil and grease to be dispersed. After application, mechanical or manual agitation should be provided to aid in the dispersing process. Apply heavily to grease or scum blankets as encountered in sewage plant digesters, lift and pumping stations. Allow to penetrate, and then use mechanical agitation to break up the blanket and emulsify the grease with the effluent.

WARNING: This product will not disperse vapors accumulated in any closed areas. Take all precautions necessary to prevent hazard from vapor accumulations.

NOTE: This product will not make spills non-hazardous. Do not flush to drains leading to sanitary or storm sewers. Please consult local environmental authorities for proper disposal.

Spills of fuel or other hazardous materials must be reported to the proper authorities, as prescribed by applicable state and Federal laws and regulations.

 **WARNING:** This product can expose you to Ethylene Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Please Recycle.

1297.031522