

TAR REMOVER

Tar & Asphalt Remover

Form: Liquid

Color: Colorless

Odor: Chlorinated Solvent

pH: N/A

Solubility (in water): Emulsifies
(in mineral spirits): Soluble

VOC Content (% by weight): N/D

Flash Point (ASTM D-7821): 110°F

Specific Gravity: 1.00 g/cm³

Density: 8.35 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Chlorinated Aromatic Hydrocarbon95-49-8

Aliphatic Petroleum Distillate64742-47-8

Surfactant9016-45-9

Uses In...

- **Floor Degreaser**
- **Rust Proof Remover**
- **Sewer Degreaser**
- **Parts Wash**
- **Bilge Cleaner**
- **Roofing Compound Remover**
- **Ink Remover**
- **Oil Tank Sludge Remover**

DIRECTIONS: Apply TAR REMOVER to the affected area, in concentrated form, with a 3 gallon pressure sprayer, or by mopping on the surface. Allow time to penetrate and dissolve the tar, asphalt or bituminous deposits for approximately 5 to 10 minutes; then rinse off with water under pressure. For light deposits of tar or asphalt, TAR REMOVER may be diluted with equal parts of an economical solvent such as mineral spirits.

NOTE: Use with care on automotive finishes to prevent damage to air dried painted surfaces.

HMIS			NFPA		
Health	2	Severe 4	Extreme	Health	2
Flammability.....	2	Serious 3	High	Flammability.....	2
Reactivity.....	0	Moderate 2	Moderate	Reactivity.....	0
Personal Protection.....	X	Slight 1	Slight	Special Precautions.....	None
		Minimal 0	Insignificant		