

DEFLECT

Ultra-Strength Urinal and Drain Cleaner

Form: Liquid

Color: Clear, Red

Odor: Pleasant

pH: No data available

Solubility (in water): Soluble
(in mineral spirits): No data available

VOC Content (% by weight): 0%

Flash Point: No data available

Specific Gravity: 1.2 g/cm³

Density: 9.22 lbs/gal

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Urea Monohydrochloride	506-89-8
Water	7732-18-5
Hydroxyphosphono Acetic Acid	23783-26-8
Acid Red 2	845-10-3

Use in...	
•	Restrooms
•	Offices
•	Gyms
•	Restaurants
•	Hotels
•	Schools
•	Maintenance Departments

URINAL TREATMENT: For best and fastest results, add DEFLECT to urinals at the end of day or when use is slowest. Allow DEFLECT to remain in the urinal for 20 minutes minimum to overnight. Shut off automatic flush if necessary during treatment. For slow-draining urinals, pour 16 ounces of DEFLECT into the urinal as follows:

1. During the first two weeks, apply DEFLECT 3 times a week at end of day.
2. During the next six weeks, apply DEFLECT once a week at end of day.
3. Beginning the third month, apply DEFLECT once a month as regular maintenance.

For urinals that drain normally, apply 16 ounces of DEFLECT once a month to maintain full flow in the drain lines. DEFLECT also attacks and removes the primary source of odors in urinals.

PLEASE NOTE: This product may have an adverse effect on some porcelain, ceramic or antique finishes, terrazzo, and polished metallic finishes. This product should not be used on colored grout, marble, or glazed surfaces. If uncertain, test on an inconspicuous area before using.

HMIS®		NFPA®	
Health	2	Severe 4	Extreme
Flammability	0	Serious 3	High
Physical Hazard	0	Moderate 2	Moderate
Personal Protection	X	Slight 1	Slight
		Minimal 0	Insignificant
			Health
			2
			Flammability
			0
			Reactivity
			0
			Special Precautions
			None