

SUPREME

Multi-Purpose Cleaner & Emulsifier



Form: Liquid
Color: Clear, red-orange
Odor: Mild lavender
pH: 12.0 – 13.0
Solubility (in water): Soluble
(in mineral spirits): No data available
VOC Content (% by weight): <0.5
Flash Point (Closed Cup): >200°F
Specific Gravity: 1.03 g/ml
Density: 8.60 lbs/gal
Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Water.....	7732-18-5
Linear Alcohol Ethoxylate	34398-01-1
Sodium Tripolyphosphate	7758-29-4
Sodium Xylene Sulfonate.....	1300-72-7
Sodium Metasilicate.....	6834-92-0

Great to use for...	
<ul style="list-style-type: none"> • Dip tanks • Housekeeping • Commercial kitchens • Building maintenance • Industrial degreasing • Heavy equipment maintenance • And much more... 	
Removes...	
<ul style="list-style-type: none"> • Oil • Dirt • Grime • Soot • Inks • Blood • Road film 	<ul style="list-style-type: none"> • Salt • Food • Lipstick • Grease • Smoke • Smudges • And much more...

DIRECTIONS: Dilute one part SUPREME with water as recommended below:

For Tough Industrial Jobs (Grease, Oil, Dirt, Grime): Start with a 1:16 dilution (8 ounces per gallon) and apply with a tank sprayer or mop. Allow SUPREME to work several minutes; agitate with a brush or mop. Rinse with water or wipe clean with a mop, rag or sponge.

For Pressure Washers, Steam Cleaners, Floor Scrubbers: Dilute up to 1:100 with water (1-2 ounces per gallon). Amount used may vary depending on soil conditions and type of machine used. Road film on vehicles may require light agitation.

For Housekeeping (Floors, Walls, Kitchen Equipment, Most Washable Surfaces): Start with a 1:64 dilution (2-3 ounces per gallon), depending on soil. Apply to floors with mop or tank sprayer. For daily mopping, no rinsing is necessary.

For Spot Cleaning: To remove food, lipstick, grease, smoke, dirt and smudges from countertops, stainless steel, doors, walls and woodwork, dilute 1:20 (1 ounce per pint) and apply using a trigger sprayer. Wipe with a clean dry cloth.

For Concrete with Oil and Grease Penetration: Scrape off excess. Dilute 1:8 (16 ounces per gallon) and apply generously. Let stand 15 minutes, agitate with stiff bristle brush. Rinse with hose.

CONSULT PRODUCT LABEL FOR COMPLETE DIRECTIONS.

HMIS®				NFPA®	
		Severe	4	Extreme	
Health	2	Serious	3	High	Health
Flammability.....	0	Moderate	2	Moderate	Flammability.....
Reactivity.....	0	Slight	1	Slight	Reactivity.....
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions.....
					None