

LIQUI-GEM EMERALD

Crosslinked Acrylic Floor Finish

Form: Liquid

Color: White

Odor: Mild

pH: 8.0 - 8.75

Solubility (in water): Soluble
(in mineral spirits): Insoluble

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): N/A

Specific Gravity: 1.03 ± 0.05 g/cm³

Density: 8.60 ± 0.05 lbs/gal

Storage Stability (at 70°F): 1 year
 (Damaged by Freezing)

<u>Ingredients</u>	<u>C.A.S. #</u>
Diethylene Glycol Methyl Ether.....	111-77-3
Zinc Ammonium Carbonate	38714-47-5
Dibutyl Phthalate	84-74-2
Tributoxyethyl Phosphate	78-51-3

Other EMERALD Uses:

- **Desk Top Sealer**
- **Marble Polish**
- **Mold Release**
- **Acrylic Floor Sealer**
- **Concrete Floor Finish**
- **Wood Floor Sealer**
- **Non-Slip Floor Coating**

DIRECTIONS: APPLICATION: Thoroughly strip, rinse and allow the floor to dry. Ensure that all previous wax coatings have been removed and that stripper is neutralized. Apply 3 to 4 coats of EMERALD allowing 30 minutes of drying time between coats.

MAINTENANCE: Damp mop or sweep nightly, or as frequently as necessary, to keep the surface clean and free of dirt, dust and other foreign matter. When traffic wear has reduced the luster and general appearance, surface clean with a solution of 2 to 3 ounces of WASH per gallon of warm water. Use this solution either for damp mopping or soft brush machine scrubbing; rinse off solution, then apply 1 to 2 coats of EMERALD.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health	1
Flammability	Moderate	2	Moderate	Flammability	1
Reactivity	Slight	1	Slight	Reactivity	0
Personal Protection	Minimal	0	Insignificant	Special Precautions	None