



# Liqui-Gem

# SETTING

## RESILIENT FLOOR SEALER

WORKS ON TERRAZZO, SLATE, VINYL

SUITABLE FOR BUFFING OR BURNISHING OPERATIONS

### KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: ■ 1 ■ 5 ■ 20 ■ 35 ■ 55 Gallon(s)

# Liqui-Gem SETTING



PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com



# Liqui-Gem

# SETTING

**DISPOSAL:** Offer empty container for recycling.  
If recycling is not available, discard container  
in trash.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

**NFPA® RATINGS:**

Health: 0; Flammability: 0; Reactivity: 0

**INGREDIENTS/CAS #:**

Water/7732-18-5; Acrylic Polymer/Proprietary;  
Diethylene Glycol Monoethyl Ether/111-90-0;  
Tributoxyethyl Phosphate/78-51-3; Zinc  
Oxide/1314-13-2

**APPLICATION DIRECTIONS:**

- Remove any previous coatings or finishes using **LIQUI-GEM MARQUISE CUT**.
- Neutralize stripper residue utilizing **LIQUI-GEM BALANCE**.
- Rinse floor with water and allow to dry completely.
- Apply **LIQUI-GEM SETTING** using a cotton string mop or lamb's wool applicator.
- Allow first coat to dry 30 minutes before applying a second coat.
- For best results, apply 2 or more coats of **LIQUI-GEM SAPPHIRE, EMERALD, or DIAMOND** floor finishes.

KEEP FROM FREEZING.



Please Recycle.

1710.051115