

LIQUI-GEM SETTING

Resilient Floor Sealer

Form: Liquid

Color: Opaque White

Odor: Mild

pH: 8.0 - 8.5

Solubility (in water): Soluble
(in mineral spirits): Insoluble

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): N/A

Specific Gravity: 8.39 ± 0.05 lbs/gal

Density: 1.005 ± 0.05 g/cm³

Storage Stability (at 70°F): 1 year
 (Damaged by Freezing)

<u>Ingredients</u>	<u>C.A.S. #</u>
Diethylene Glycol Methyl Ether.....	111-77-3
Zinc Ammonium Carbonate	38714-47-5
Dibutyl Phthalate	84-74-2
Tributoxyethyl Phosphate	78-51-3

Use on such floors as...	
•	Ceramic Tile
•	Magnasite
•	Slate
•	Vinyl
•	Cork
•	Travertine
•	Rubber
•	Linoleum
•	Concrete

DIRECTIONS: APPLICATION: Thoroughly strip, rinse and allow the floor to dry. Ensure that all previous wax coatings have been removed and that stripper is neutralized. Apply SETTING using a cotton mop or lambswool applicator. For really porous floors, apply a second coat after the first has thoroughly dried. Then apply two coats of a floor finish, based on what type of shine is desired on the floor.

HMIS				NFPA	
	Severe	4	Extreme		
Health	Serious	3	High	Health	1
Flammability.....	Moderate	2	Moderate	Flammability	0
Reactivity.....	Slight	1	Slight	Reactivity	0
Personal Protection	Minimal	0	Insignificant	Special Precautions.....	None

KEEP FROM FREEZING.

Share Corporation • P.O. Box 245013 • Milwaukee, WI 53224 • 800-776-7192