

UNITE

Two Part Epoxy Resin Stick



Form: Solid

Color: White / beige

Odor: Pungent, strong sulfur

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): No information

available

VOC Content (% by weight): No
information available

Flash Point (Setaflash): > 199.9°F

Specific Gravity: 1.95 g/cm³

Density: 16.27 lbs/gal

Shelf Stability (at 75°F): 24 months
minimum

Ingredients

C.A.S. #

Bisphenol-A-(epichlorhydrin);
 epoxy resin 25068-38-6
 2,4,6-tris(dimethylaminomethyl)
 phenol..... 90-72-2
 Crystalline silica non-respirable..... 14808-60-7

Other Uses...
<ul style="list-style-type: none"> • Gas Tanks • Radiators • Bathroom Fixtures • Tile • Plumbing • Cars • Boats • Downspouts • Gutters & Leaders • Garbage Cans • Valves • Swimming Pools • Aluminum & Iron Railings • Will withstand dilute acids and caustics.

DIRECTIONS: CUT or twist off required amount with gloved hand. **MIX** by kneading with gloved fingers to a uniform color. If mixing is difficult, warm UNITE to room temperature or slightly above. **APPLY** to surface to be repaired within 2 minutes of mixing. For best adhesion, force into any cracks or holes and strike off excess material, preferably with a tool moistened with clean water. When applying to a damp, wet or slowly leaking area, work the mixed epoxy putty forcefully into the surface and apply pressure until adhesion begins to take effect.

For best results: Use damp, gloved fingers for easier mixing, application and a smooth appearance of the cured compound. Remove excess material before hardening begins.

Curing: UNITE has a 3 to 5 minute work life. Functional cure occurs in 60 minutes.

HMIS®			NFPA®		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	2
Flammability	Moderate	2	Moderate	Flammability	1
Physical Hazard	Slight	1	Slight	Reactivity	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions	None