

RESPONSE:**IF INHALED:**

Move exposed person to fresh air. Get medical attention if symptoms occur. No symptoms expected.

IF INGESTED:

Wash out mouth with water. Do not induce vomiting. Get medical attention if nausea or stomach pains occur.

IF ON SKIN:

Remove contaminated clothing and shoes. Wash skin with soap and water. Get medical attention if irritation symptoms occur. High pressure injection under skin requires immediate medical attention.

IF IN EYES:

Check for and remove any contact lenses. Immediately flush eyes with running water

for at least 5 minutes, keeping eyelids open. Get medical attention if redness or irritation persists.

STORAGE:

Store in cool dry area in original or equivalent container in accordance with all regulations. Do not expose to extremem heat or flame. Store below 65°C, away from strong oxidizers and acids.

DISPOSAL:

Generation of waste should be avoided or minimized where possible. Empty containers may contain residue. Dispose of non-recyclable material via licensed waste disposal operator. Follow all applicable regulations.

INGREDIENTS:

Petroleum Oil (64742-52-5); Rheological Thickener (68953-58-2); EP Additives (Proprietary); Rust Inhibitors (Proprietary).

NFPA® RATINGS:

Health: 0; Flammability: 1; Reactivity: 0

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

1849.02087



RED GEM

HI-TEMP RED GREASE



Share Corporation's **RED GEM HI-TEMP RED GREASE** is a Super Impact, Non-Melt Extreme Pressure grease. It contains extreme pressure additives for high shock and impact resistance and high loads. It's thick bentone based formula is fortified with excellent inhibitors and tackifiers for all weather performance, washout resistance, and rust and corrosion prevention. **RED GEM HI-TEMP RED GREASE** can be used for hundreds of automotive, marine, and agricultural applications.

TEMPERATURE RANGE FROM 0° to 550°F.

DIRECTIONS FOR USE:

Pump in **RED GEM HI-TEMP RED GREASE** until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new **RED GEM HI-TEMP RED GREASE**.

SOLD BY:

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com