



HANG ON

DO ALL PATCHING MORTAR

Designed for general purpose
and high performance concrete repair
or resurfacing applications.

- Heavy Duty - Over 4500 PSI • Corrosion Inhibitor Included
- Portland Cement Based • One Component - Just Add Water
- Shrinkage-Compensated • Polymer Modified

DANGER

Causes serious eye damage. Causes skin irritation.
May cause respiratory irritation. Causes damage to organs
(Lung) through prolonged or repeated exposure (inhalation).

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 5 GALLONS



DANGER: Causes serious eye damage.
Causes skin irritation. May cause respiratory
irritation. Causes damage to organs
(Lung) through prolonged or repeated
exposure (inhalation).

PREVENTION: Wear protective
gloves and eye/face protection. Use only
outdoors or in a well-ventilated area. Do
not breathe dust/gas/mist/vapors. Do
not eat, drink or smoke when using this
product. Wash with plenty of water and
soap thoroughly after handling.

IF IN EYES: Rinse cautiously with water
for several minutes. Remove contact
lenses, if present and easy to do.
Continue rinsing. Immediately call a
POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Wash with plenty
of soap and water. Take off contaminated
clothing and wash before reuse.

STORAGE: Store in a well-ventilated
place. Keep container tightly closed.
Store locked up.

DISPOSAL: Dispose of contents/
container to hazardous or special waste
collection point.

WARNING: This product contains a
chemical known to the state of California
to cause cancer. This product contains a
chemical known to the state of California
to cause reproductive/developmental
effects.

HANG ON is a 1 component, polymer modified, high performance
concrete repair and resurfacing mortar. **HANG ON** is simply mixed with
water and applied from featheredge to over 2" thick in one or more
applications. See below mixing guidelines. Apply horizontal, vertical or
overhead. Product sets in 20 to 45 minutes and ready for light traffic in
3 to 4 hours at 70 degrees Fahrenheit.

For Best Results:

Apply to a clean, dry sound substrate above 40°F. Rub or scratch part
of the mixed material onto surface just prior to application. Do not allow
rub or scratch coat to dry before application. Check moisture content
(mat test) prior to applying any waterproof topping. Do not retemper
already mixed material. Reasonable variations from the above data can
be expected depending on field conditions, surface preparation, curing,
contractor expertise and evaluation and/or handling of test cylinders.

Surface Preparation:

Surface preparation is critical to achieve long lasting results. Existing
concrete surface shall be clean, sound, and free of oil, grease, laitance,
curing compounds or any other foreign substance. Areas treated with
product must be free of dust and any foreign matter prior to topping
application. On highly porous substrates, contact the manufacturer for
recommended application procedures.

Mixing Guidelines:

Approximately 1/2 parts of water is required to mix 50 lb of product
for patching applications. Always add and mix product into water. For
applications 1/2" to 2" or more, extend product up to 40% with clean
and dry 3/8" sea gravel.

Application:

Trowel apply. Rub or scratch part of the mixed material onto surface
just prior to application.

Curing:

Rapid drying of cement-based products may cause cracking or
de-bonding. Avoid applications in high winds, excessive heat or blowing
air directly on freshly placed product. If these conditions apply, damp
cure for 1-3 days. Curing compounds, wet burlap or polyethylene will
reduce rapid drying but may cause color change or mar product
surface. Allow 3-4 hours for light traffic on horizontal repairs.

INGREDIENTS/CAS#:

Portland cement (65997-15-1); Calcium
Aluminate Cement (65997-16-2);
Crystalline silica (14808-60-7); Kaolin
(1332-58-7)

NFPA® RATINGS:

Health: 3; Flammability: 0; Reactivity: 0



Please Recycle.

1859.060815

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com