



TRIDENT

WATER TREATMENT

TOWERGUARD POLYCLEAN

COOLING TOWER WATER TREATMENT

WARNING:

May be corrosive to metals.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

TRIDENT

WATER TREATMENT

TOWERGUARD POLYCLEAN



P.O. Box 245013
Milwaukee, WI 53224
(800) 776-7192
www.sharecorp.com



WARNING:

May be corrosive to metals.

Keep only in original container.
Absorb spillage to prevent material damage.

Store in corrosive resistant container with a resistant inner liner.

DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water/7732-18-5; Acrylamide Copolymer/
Proprietary; Potassium Hydroxide/1310-58-3



Please Recycle.

TRIDENT TOWERGUARD POLYCLEAN is a cooling tower water treatment that gradually removes and prevents sludge, silt and dirt deposits from fouled recirculating cooling systems. Maintenance of a cooling tower system is very important in maximizing system efficiency, increasing operating efficiency, minimizing bleed-off and reducing downtime. **TRIDENT TOWERGUARD POLYCLEAN** keeps heat transfer surfaces clean and minimizes maintenance requirements by reducing adhesion of scale forming minerals by holding scale material in suspension. The end result of using **TRIDENT TOWERGUARD POLYCLEAN** is scale reduction and increased cooling tower efficiency.

DIRECTIONS:

TRIDENT TOWERGUARD POLYCLEAN is for use in cooling towers 200 tons or greater. **TRIDENT TOWERGUARD POLYCLEAN** can be added to sump, tower basin or directly in circulation line.

Initial Application: Add 1 gallon of **TRIDENT TOWERGUARD POLYCLEAN** for every 3000 gallons of cooling tower water.

Daily Application: The feed rate for **TRIDENT TOWERGUARD POLYCLEAN** is 1 gallon for every 1000 gallons of cooling tower water.

Rapid Cleaning Application: Add 2 gallons of **TRIDENT TOWERGUARD POLYCLEAN** for every 3000 gallons of cooling tower water until bleed-off occurs.