

Rubber In a Can

- SEALS OUT MOISTURE
- PAINTABLE
- PREVENTS RUST FORMATION
- CONTAINS NO OZONE DEPLETING CHEMICALS

FOR INDUSTRIAL/PROFESSIONAL USE ONLY.
NOT FOR RETAIL SALE.

See back panel for additional precautions.

NET WEIGHT: 16 OZ. (454 g)

RUBBER IN A CAN provides superior protection for fender replacements, section repairs and weld joints. It also depresses sound, retards salt corrosion, and seals water leaks. RUBBER IN A CAN may be used on concrete and asphalt driveways, gutters and flashings and roofs.



DANGER:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye damage. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs (central nervous system, eyes, kidney, liver, skin, and respiratory system) through prolonged or repeated exposure. May be fatal if swallowed and enters airways

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

RESPONSE

If exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

DISPOSAL

Dispose of contents/container to an approved waste disposal plant.

INGREDIENTS/CAS

CALCIUM CARBONATE (1317-65-3), TOLUENE (108-88-3), METHYL ACETATE (79-20-9), ACETONE (67-64-1), SOLVENT NAPHTHA (64742-94-5), XYLENE (1330-20-7), CARBON BLACK (1333-86-4), PETROLEUM DISTILLATES (64742-89-8)

KEEP OUT OF REACH OF CHILDREN

Refer to SDS for further information.

DIRECTIONS

SHAKE WELL BEFORE USING. Make sure surface is clean, dry and free of dirt and rust. Hold can 12 inches from surface. Spray a thin even coat building up to the desired thickness. Remove overspray with a cloth dampened with kerosene. Coverage: 10 to 20 square feet per can. Temperature: Both surface and at use temperature should be between -10 °F to 150 °F.

WARNING

This product contains a chemical(s) known to the state of California to cause cancer and birth defects or other reproductive harm.

Sold by:



8002.042615

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com