

# RUBBER IN A CAN KLEAR

## Protective Flexible Rubber Coating

**Form:** Aerosol Liquid

**Color:** Clear

**Odor:** Solvent

**pH:** N/A

**Solubility (in water):** Negligible  
**(in mineral spirits):** No data available

**VOC Content (% by weight):** 22.5

**Flash Point:** -156°F (Propellant)

**Specific Gravity:** 0.827 g/ml

**Density:** 6.90 lbs/gal

**Storage Stability (at 70°F):** 1 year

**Ingredients**

**C.A.S. #**

Methyl Acetate .....	79-20-9
Propane/Isobutane/N-butane .....	68476-86-8
Petroleum Distillates .....	64742-89-8
Xylene .....	1330-20-7
Acetone .....	67-64-1

**Great for use on...**

- **Concrete and Asphalt Driveways**
- **Gutters and Flashings**
- **HVAC Equipment**
- **Construction Equipment**
- **Roofs**
- **Gas Tanks**
- **Trunk Decks**
- **Underbodies and Fender and Panel Replacements**

**DIRECTIONS:** SHAKE WELL BEFORE USING. Make sure surface is clean, dry and free of dirt and rust. Hold can 12 inches from surface. Spray a thin even coat building up to the desired thickness. Remove overspray with a cloth dampened with kerosene.

**Coverage:** 10 to 20 square feet per can.

**Temperature:** Both surface and at use temperature should be between -10°F to 150°F.

HMIS®				NFPA®	
		Severe	4	Extreme	
Health .....	2*	Serious	3	High	Health .....
Flammability .....	4	Moderate	2	Moderate	Flammability .....
Reactivity .....	1	Slight	1	Slight	Reactivity .....
Personal Protection .....	B	Minimal	0	Insignificant	Special Precautions .....
					None