



OPEN GEAR LUBE

HIGH ADHESION SPRAY LUBRICANT

For Open Gears, Chains, or
Wire Ropes on Industrial Machinery

Temperature Range of 20°F to 175°F
Contains No Chlorinated
or Fluorinated Solvents

DANGER:

Extremely flammable aerosol contains gas under pressure; May explode if heated.

KEEP OUT OF REACH OF CHILDREN

NET WEIGHT: 12 ounces (340 grams)

OPEN GEAR LUBE forms a tough, solid, lubricating film for use on gears, sprockets, wire ropes, cables, chains, on industrial machinery and heavy construction equipment. It seals out moisture and repels water to prevent rust and corrosion. The excellent stretching characteristics of **OPEN GEAR LUBE** allow it to completely cover parts and machinery with lubricant, which extends the life of machinery and reduces downtime. It protects gears under excessive loads and reduces noise. Its effective temperature range is 20°F to 175°F.



DANGER:

Extremely flammable aerosol contains gas under pressure; May explode if heated. Causes skin and eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

PREVENTION:

Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Wash hands thoroughly after handling. Wear protective gloves.

RESPONSE:

Avoid breathing fumes, mist, vapors, and spray. Use only outdoors in a well-ventilated area.
If on skin: wash with plenty of water. If skin irritation occurs, get medical advice or attention. Take off contaminated clothing and wash before reuse.
If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
If swallowed: immediately call a poison center or a doctor. Do NOT induce vomiting.

Store locked up. Dispose of contents/container in accordance with local, state, and national guidelines.

INGREDIENTS/CAS#:

Petroleum Resins (64742-16-1); Heptane (142-82-5); Propane/n-Butane (68476-86-8); Hydrotreated Petroleum Oils (64742-57-0).

NFPA® RATINGS:

Health: 1; Flammability: 3; Reactivity: 0

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

DIRECTIONS:

Shake Well Before Using. Remove cap and hold can approximately 6 to 8 inches from surface to be sprayed. Apply a continuous film of lubricant, turn on machinery and allow the lubricant to spread over all working surfaces. Apply a second thinner coat to insure adequate protection. Reapply as needed. After use, turn can upside down and spray for a few seconds to clear the nozzle.

Sold by:

8012.021815