

Ceiling Tile Whitener – New White

Safety Data Sheet



SECTION 1: Product and company identification

Product name : Ceiling Tile Whitener – New White
Use of the substance/mixture : Aerosol
Paint.
Product code : 801401
Company : Share Corporation
P.O. Box 245013
Milwaukee, WI 53224 - USA
T (414) 355-4000
Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222
Liquefied gas H280
Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 3 H336
Asp. Tox. 1 H304

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol
Contains gas under pressure; may explode if heated
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness

Precautionary statements (GHS-US) :

Keep away from heat, sparks, open flames, hot surfaces, Do not smoke. - No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use
Avoid breathing fume, vapors, spray
Wash thoroughly after handling
Use only outdoors or in a well-ventilated area
Wear protective gloves, eye protection
If swallowed: Immediately call a doctor, a POISON CENTER, Do NOT induce vomiting
If on skin: Wash with plenty of water
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Call a doctor, a POISON CENTER if you feel unwell
Specific treatment (see First aid measures on this label)
Do NOT induce vomiting
If skin irritation occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash before reuse
Store in a well-ventilated place. Keep container tightly closed
Store locked up
Protect from sunlight. Store in a well-ventilated place
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Ceiling Tile Whitener – New White

Safety Data Sheet



SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Petroleum gases, liquefied, sweetened, Petroleum gas, [A complex combination of hydrocarbons obtained by subjecting liquefied petroleum gas mix to a sweetening process to convert mercaptans or to remove acidic impurities. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).]	(CAS No) 68476-86-8	15 - 40	Flam. Gas 1, H220 Compressed gas, H280 Muta. 1B, H340 Carc. 1A, H350
heptane, n-heptane	(CAS No) 142-82-5	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
acetone, propan-2-one, propanone	(CAS No) 67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
ethanol	(CAS No) 64-17-5	5 - 10	Flam. Liq. 2, H225 STOT SE 3, H336
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-47-8	3 - 7	Flam. Liq. 4, H227 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Artificial respiration and/or oxygen if necessary.
First-aid measures after skin contact	: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation.
Symptoms/injuries after inhalation	: Harmful if inhaled.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical powder. Adapt extinguishing media to the environment.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable aerosol. Under fire conditions closed containers may rupture or explode.
Explosion hazard	: Contains gas under pressure; may explode if heated.
Reactivity	: Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk.
------------------	---

Ceiling Tile Whitener – New White

Safety Data Sheet



6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Eliminate every possible source of ignition. Collect spillage.

Methods for cleaning up : Take up liquid spill into inert absorbent material.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pressurized container. Do not puncture, incinerate or crush.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible products : Refer to Section 10 on Incompatible Materials.

Heat-ignition : KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.

Storage area : Store in a cool area. Store away from heat. Keep locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

heptane, n-heptane (142-82-5)		
ACGIH	ACGIH TWA (ppm)	400 ppm
ethanol (64-17-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
ACGIH	Remark (ACGIH)	URT irr
acetone, propan-2-one, propanone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Aerosol. white, opaque liquid.

Odor : Petroleum-like.

Odor threshold : No data available

pH : No data available

Melting point : No data available

Ceiling Tile Whitener – New White

Safety Data Sheet



Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.87 g/ml
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: > 60 cSt
Viscosity, dynamic	: No data available
VOC content	: 51 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

No flames, No sparks. Eliminate all sources of ignition. Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Can affect plastics.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Literature)
ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
ATE CLP (oral)	10740.000 mg/kg body weight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.

Ceiling Tile Whitener – New White

Safety Data Sheet



Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: Harmful if inhaled.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Likely routes of exposure	: Inhalation;Ingestion.;Skin and eyes contact.

SECTION 12: Ecological information

12.1. Toxicity

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
LC50 fish 1	> 100 mg/l (Pisces)
EC50 Daphnia 1	> 100 mg/l (Invertebrata)
Threshold limit algae 1	> 100 mg/l (Algae)
ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	9300 mg/l (48 h; Daphnia magna)
LC50 fish 2	13000 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	10800 mg/l (24 h; Daphnia magna)
Threshold limit other aquatic organisms 1	65 mg/l (72 h; Protozoa)
Threshold limit algae 1	1450 mg/l (192 h; Microcystis aeruginosa; Growth rate)
Threshold limit algae 2	5000 mg/l (168 h; Scenedesmus quadricauda; Growth rate)

12.2. Persistence and degradability

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.
ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O /g substance
Chemical oxygen demand (COD)	1.70 g O /g substance
ThOD	2.10 g O /g substance
BOD (% of ThOD)	0.43 % ThOD

12.3. Bioaccumulative potential

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Log Pow	6 - 8.2
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
ethanol (64-17-5)	
BCF fish 1	1 (72 h; Cyprinus carpio)
Log Pow	-0.31 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description	: UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
UN-No.(DOT)	: UN1950
Proper Shipping Name (DOT)	: Aerosols flammable, (each not exceeding 1 L capacity)
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Ceiling Tile Whitener – New White

Safety Data Sheet



Hazard labels (DOT) : 2.1 - Flammable gas



Marine pollutant : Yes (IMDG only)



DOT Packaging Non Bulk (49 CFR 173.xxx) : None
 DOT Packaging Bulk (49 CFR 173.xxx) : None
 DOT Special Provisions (49 CFR 172.102) : N82
 DOT Packaging Exceptions (49 CFR 173.xxx) : 306
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
 DOT Vessel Stowage Location : A
 DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
 Proper Shipping Name (IMDG) : Aerosols, Ltd. Qty.
 Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No. (IATA) : UN1950
 Proper Shipping Name (IATA) : Aerosols, Ltd. Qty.
 Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

acetone, propan-2-one, propanone (67-64-1)	
Not listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb

California Proposition 65 - This product does not contain trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1

Ceiling Tile Whitener – New White

Safety Data Sheet




Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Liquefied gas	Gases under pressure Liquefied gas
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.