



# CEILING TILE WHITENER

**NEW WHITE  
ACOUSTIC TILE REJUVENATOR**

**CEILING TILE PAINT FOR  
TEXTURED AND ACOUSTICAL CEILINGS**

**Covers Discoloration, Stains and Water Spots**

**V.O.C. Compliant**

**DANGER:**

Extremely Flammable Aerosol. Contains gas under pressure:  
May explode if heated.

**NET WEIGHT:** 16.0 ounces (454 grams)

Use CEILING TILE WHITENER to cover water spots, stains and blackening around air conditioner vents. Primer is not required. It dries instantly to a unique micro-void finish to maintain acoustic properties. It will not harm tiles or cause them to sag or warp. Easy to use, because the 360° valve sprays in any direction.



**DANGER:**

Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

**PREVENTION:**

Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection.

**RESPONSE:**

**IF ON SKIN:** Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

*Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area.*

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

**IF SWALLOWED:** Immediately call a poison center or doctor. Do NOT induce vomiting.

**STORAGE:**

Store locked up.

**DISPOSAL:**

Dispose of contents and container in accordance with local, state, and national regulations.

**INGREDIENTS/CAS#:**

Propane/n-Butane (68476-86-8); Isoparaffinic Hydrocarbon (64742-47-8); Acetone (67-64-1); Titanium Dioxide (13463-67-7); Ethyl Alcohol (64-17-5); Heptane (142-82-5).

**NFPA® RATINGS:**

Health: 2; Flammability: 3; Reactivity: 0

**DIRECTIONS:**

Clean surface thoroughly to remove grease, dust, and other foreign matter. Shake can vigorously before and during use. From a distance of 12 inches, spray to coat surface lightly. Allow to dry, then follow with another light coat. Apply at temperatures above 65°F. One can covers 12-15 (2' x 4') tiles or 120 sq. ft. NOTE: Following use, invert can and spray a short burst to clear nozzle for storage. If nozzle becomes clogged, remove and hold under running warm water.

Sold by:

8014.030315

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • [www.sharecorp.com](http://www.sharecorp.com)