

HI-YO SILVER

Protective Flexible Durable White Coating

Form: Aerosol

Color: Silver Liquid

Odor: Aromatic

pH: No Data Available

Solubility (in water): No Data Available

(in mineral spirits): No Data Available

VOC Content: < 50 %

Flash Point (ASTM D-7821): -2.2 °F

Specific Gravity: 0.77 – 0.85 g/ml

Storage Stability (at 70°F): 1 year

Ingredients

VM&P Naphtha

Toluene

Propane

Heptane

N-Butane

Features

- **Flexible Coating**
- **Won't Crack or Peel**
- **Protects Against Corrosion**
- **Won't Freeze**
- **Seals Leaky Roofs!**

C.A.S.

64742-82-5

13463-67-7

74-98-6

142-82-5

106-97-8

DIRECTIONS: Ensure surface is clean and dry. Shake at least 1 minute and occasionally during use. Spray surface with steady even strokes 2-10 inches away from surface. If multiple coats are desired, allow 30 minutes between coats. After use clear sprayhead by inverting can and spraying for 3 seconds.

CONSULT PRODUCT LABEL FOR DETAILED USE DIRECTIONS.

| HMIS | | | NFPA | | |
|-------------------|----------|---|----------|-------------------|---|
| | Severe | 4 | Extreme | | |
| Health | Serious | 3 | High | Health | 2 |
| Flammability..... | Moderate | 2 | Moderate | Flammability..... | 4 |
| Reactivity..... | Slight | 1 | Slight | Reactivity..... | 0 |

Share Corporation • P.O. Box 245013 • Milwaukee, WI 53224 • 800-776-7192