PENETRANT & RUST PREVENTATIVE

Quickly Penetrates Rust

Displaces Moisture

Lubricates and Prevents Corrosion

• Non-Flammable

 Non-Conductive, High Dielectric Strength: 39,500V

DANGER

Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing genetic defects (Inhalation). May cause cancer (Inhalation).

KEEP OUT OF REACH OF CHILDREN

See side panel for additional precautions.

Net Wt. 17 oz. (482 g)

FOUR WAY ACTION frees rusted and corroded screws, nuts, and bolts as well as aluminum and copper fittings. Use it to displace moisture on electronic and electrical equipment, protect metal, lubricate precision instruments and waterproof ignition systems and terminals. FOUR WAY ACTION saves production and repair costs as it protects and preserves equipment from failures due to moisture.



DANGER:

Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing genetic defects (Inhalation). May cause cancer (Inhalation).

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist, spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves, eye protection. Take off contaminated clothing and wash it before reuse.

RESPONSE:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for sourced minutes

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists:

Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Call a POISON CENTER, a doctor if you feel unwell.

STORAGE:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

DISPOSAL:

Dispose of contents/container to comply with local/regional/ national/international regulations.

DIRECTIONS:

SHAKE WELL BEFORE USING. Hold nozzle 6 to 8 inches from surface to be treated. Saturate area with **FOUR WAY ACTION**. Severely corroded parts may need additional treatment.

INGREDIENTS/CAS#:

Trichloroethylene (79-01-6); Heavy hydrotreated naphthenic distillates (64742-52-5); Hydrotreated Light Alkanes (64742-47-8); Carbon Dioxide (124-38-9).

NFPA® RATINGS: Health: 2; Flammability: 1; Reactivity: 0

WARNING: This product can expose you to Trichloroethylene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



8097 112321

Sold by:

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com