



SILICONE LUBRICANT

DRY-FILM SILICONE LUBRICANT

**MEDIUM VISCOSITY, LIGHT DUTY,
NO GUMMING, REDUCES FRICTION,
PROTECTS AND RENEWS.**

NET WEIGHT: 13 ounces (369 grams)

KEEP OUT OF REACH OF CHILDREN

DANGER: EXTREMELY FLAMMABLE

VAPOR HARMFUL. Harmful or Fatal if swallowed.
Contents under pressure. See side panel for additional
precautions and first aid instructions.

DESCRIPTION

SILICONE LUBRICANT is a general purpose silicone lubricant formulated to stop sticking, binding and squeaking. It is a unique formulation of a reacted grade silicone and fast evaporating solvents, with fine mist spray pattern that allows for even and controlled silicone distribution. When used as directed does not cause "fish eyes" in paint, and is therefore useful in auto body shops, mold release, and other applications where paintability is required. SILICONE LUBRICANT is also excellent for metal-to-metal, aluminum, rubber & plastic lubrication, thread & fiber lubes, and rubber & plastic mold release applications.

APPLICATIONS

Automotive Industry - Prevents freezing of lock mechanisms, lubricates rubber door and window seals, lubricates and protects parts.

Packaging & Processing Industry - Lubricates movable parts on all packaging and processing machinery. Helps reduce rusting of exposed metal.

Textile Industry - Reduces friction on ironing and pressing equipment. Use on cutting tables to prevent binding and provide smooth and even cutting.

Mold Release - Excellent for rubber, plastic & paintable mold release applications. SILICONE LUBRICANT can also be used on vending equipment, molding equipment, dry cleaning equipment and other applications where lubrication is required.

DIRECTIONS

Thoroughly clean surface to be sprayed. Hold the SILICONE LUBRICANT can 8" to 10" from surface. Spray lightly with a sweeping motion. Avoid over-spraying. On sucking parts, work back and forth to allow good penetration. Wipe off excess with a clean cloth.

DANGER: EXTREMELY FLAMMABLE

CAUTION: Vapor harmful, harmful or fatal if swallowed. Use only with adequate ventilation. Keep out of reach of children. Avoid excessive inhalation of fumes and repeated or prolonged contact with skin. Contents under pressure. Do not expose to heat or store at temperatures exceeding 120°F. Do not puncture or incinerate container. Wrap empty container and put in trash collection.

FIRST AID:

If Swallowed: Do not induce vomiting. Obtain immediate medical assistance.

If Inhaled: Remove person to fresh air. Perform artificial respiration if indicated. Obtain immediate medical assistance.

If In Eyes: Flush with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical assistance.

If On Skin: Thoroughly wash with soap and water. Obtain medical attention if irritation persists.

This product is designed exclusively for industrial and institutional use by trained personnel. This product is sold as is and the manufacturer makes no warranty, express or implied, of merchantability, fitness for a particular purpose or otherwise.

This product contains

	CAS No.
Heptane.....	142-82-5
N-Butane (Propellant).....	106-97-8
Propane (Propellant).....	74-98-6
Silicone Fluid.....	68952-01-2

8096-012009

Health	2	HMSI	Severe 4	NFPA	Extreme 4
Flammability	4	Serious	3	High Moderate	2
Reactivity	0	Moderate	2	Slight	0
Personal Protection	G	Slight	1	Insignificant	
		Minimal	0		

Share Corporation
P.O. Box 245013
Milwaukee, WI 53224
(800) 776-7192
www.sharecorp.com



Nonfood Compounds
Program Listed H2
Registration # 141729