

DI-LUBE

Aerosol Cutting & Tapping Lubricant

Form: Liquid

Color: Dark Amber

Odor: Solvent

pH: N/A

Solubility (in water): Negligible
(in mineral spirits): Soluble

VOC Content (% by weight): 9.0%

Flash Point (ASTM D-7821): N/D

Specific Gravity: <1.00 g/cm³

Density: 8.35 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Hydrotreated Light

Naphthenic Oil.....64742-53-6

White Mineral Oil.....8042-47-5

Naphthenic Distillate (Heavy)64741-96-4

Liquefied Petroleum Gas68476-85-7

Great to use for...

- Grinding
- Cutting
- Rolling
- Milling
- Drilling
- Tapping
- Boring
- Threading

Provides Protection by...

- Reducing heat buildup
- Producing cleaner cuts
- Prolonging life of the tools
- Protecting metal from rust and corrosion

DIRECTIONS: Hold nozzle 8 - 10 inches from part being machined. Spray DI-LUBE to thoroughly cover part and cutting tool. For more accurate application, insert the extension tube into the actuator.

HMIS				NFPA		
Health	2	Severe	4	Extreme	Health.....	2
Flammability.....	4	Serious	3	High	Flammability.....	4
Reactivity.....	0	Moderate	2	Moderate	Reactivity.....	0
Personal Protection.....	X	Slight	1	Slight	Special Precautions.....	None
		Minimal	0	Insignificant		