



**THICK CLINGING LUBRICANT
 PROTECTS AGAINST
 SEIZING • GALLING • CORROSION
 GALVANIC PITTING • RUST
 OF ALL THREADED PARTS**

Net Weight: 13 ounces (369 g)

DANGER: FLAMMABLE

Harmful or Fatal if Swallowed.
 CONTENTS UNDER PRESSURE.

See back panel for further cautions and first aid instructions.
KEEP OUT OF REACH OF CHILDREN

Metal parts won't corrode or lock when you coat them with RYBS from Share Corporation. This clinging lubricant contains moly, graphite and aluminum to prevent parts from seizing and galling when operating under intense heat and pressure. RYBS has been proven in temperatures ranging from -20°F to 2,000°F. When sprayed onto threaded components, RYBS provides a lubricating film between parts that prevents corrosion and seizing. It's an excellent general purpose lubricant for metal to metal contacts such as hinges and seals around boiler inspection ports. RYBS contains no chlorinated or fluorinated solvents.

DIRECTIONS

Surface must be free of dirt, grease and oil. Shake can for at least 30 seconds. In upright position, hold nozzle 8 to 10 inches from surface and apply by spraying RYBS in short bursts. Assemble and wipe off excess.

DANGER: FLAMMABLE

Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID:

If In Eyes: Flush with large amounts of cool water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention.

If On Skin: Wash with soap and water. If irritation persists seek medical attention.

If Inhaled: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

If Ingested: Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

8229-010311

Health	1	HMIS	Severe	4	NFPA	Extreme	
Flammability	3		Serious	3		High	
Reactivity	1		Moderate	2		Moderate	
Personal Protection	G		Slight	1		Slight	
			Minimal	0		Insignificant	

This product contains

CAS No.

Heavy Naphthenic Distillate64742-52-5
Heptane142-82-5
Propane/n-Butane68476-86-8
Aluminum7429-90-5