Safety Data Sheet



SECTION 1: Product and company identification

Product name : Oven Cleaner

Use of the substance/mixture : Aerosol

Cleaner

Product code : 831701

Company : Share Corporation

P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas H280 Met. Corr. 1 H290 Skin Corr. 1A H314

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



T.

GHS05

211004

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Contains gas under pressure; may explode if heated

May be corrosive to metals

Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : Keep only in original container

Do not breathe mist

Wash thoroughly after handling

Wear protective gloves, protective clothing, eye protection, face protection

If swallowed: rinse mouth. Do NOT induce vomiting

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower

If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Immediately call a doctor, a POISON CENTER

Specific treatment (see First aid measures on this label)

Wash contaminated clothing before reuse Absorb spillage to prevent material damage

Store locked up

Store in corrosive resistant container with a resistant inner liner

Protect from sunlight. Store in a well-ventilated place

Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Date of issue: 8/17/2015 Revision date: 05/18/2015 Version: 1.0 P GHS SDS Page 1 of 7

Safety Data Sheet



Name	Product identifier	%	Classification (GHS-US)
sodium hydroxide	(CAS No) 1310-73-2	5 - 10	Met. Corr. 1, H290 Skin Corr. 1A, H314
Glycol Ether EB	(CAS No) 111-76-2	1 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT RE 2, H373 Asp. Tox. 1, H304
propane	(CAS No) 74-98-6	1 - 5	Flam. Gas 1, H220 Compressed gas, H280
isobutane	(CAS No) 75-28-5	1 - 5	Not classified
2-aminoethanol, ethanolamine	(CAS No) 141-43-5	<=1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 STOT SE 3, H335

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.

First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap

and water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May be harmful if swallowed. Causes severe skin burns and eye damage.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Harmful if swallowed. Burns to the gastric/intestinal mucosa. Gastrointestinal complaints.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Under fire conditions closed containers may rupture or explode.

Explosion hazard : Bursting aerosol containers may be propelled from a fire at high speed. Contains gas under

pressure; may explode if heated. Vapors may travel long distances along ground before

igniting/flashing back to vapor source.

Reactivity : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Evacuate area. No action shall be taken involving

any personal risk or without suitable training. Move containers away from the fire area if this can be

done without risk. Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area. Stop release. Stop leak if safe to do so.

 Date of issue: 8/17/2015
 Revision date: 05/18/2015
 Version: 1.0
 P GHS SDS
 Page 2 of 7

Safety Data Sheet



6.2. Environmental precautions

Stop leak if safe to do so. Isolate hazard area. Eliminate all ignition sources. Use ventilation/water spray/fog to disperse vapors. Prevent runoff from entering drains, sewers or waterways. Absorb and/or contain spill with inert material, then place in suitable container.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Pressurized container:

Do not pierce or burn, even after use. Keep away from heat, sparks and flame.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Intentional misuse by deliberately concentrating and

inhaling may be harmful or fatal.

Handling temperature : < 120 °F

Hygiene measures : Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Keep cool. Protect from sunlight. Store in a well-ventilated place. Store

in a dry place.

Incompatible products : acids. Oxidizing agents.

Incompatible materials : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Glycol Ether EB (111-76-2)			
ACGIH	ACGIH TWA (ppm)	20 ppm	
ACGIH	Remark (ACGIH)	Eye & URT irr	
2-aminoethanol, ethanolami	2-aminoethanol, ethanolamine (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm	
ACGIH	ACGIH STEL (ppm)	6 ppm	
ACGIH	Remark (ACGIH)	Eye & skin irr	
propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
isobutane (75-28-5)			
ACGIH	ACGIH STEL (ppm)	1000 ppm	

8.2. Exposure controls

Personal protective equipment

Gloves. Protective goggles. Use appropriate personal protective equipment when risk assessment indicates this is necessary.





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Aerosol. clear. Liquid.
Odor : slight Solvent-like odor
Odor threshold : No data available

pH : 12 - 13

Date of issue: 8/17/2015 Revision date: 05/18/2015 Version: 1.0 P GHS SDS Page 3 of 7

Safety Data Sheet



Melting point No data available : No data available Freezing point Boiling point No data available Flash point : (liquid portion) Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) No data available : No data available **Explosion limits** Explosive properties No data available Oxidizing properties : No data available : No data available Vapor pressure Relative density No data available Relative vapor density at 20 °C : No data available

Specific gravity / density : 1 g/ml

Solubility : Soluble in water. : No data available Log Pow Log Kow No data available Auto-ignition temperature : No data available Decomposition temperature No data available No data available Viscosity Viscosity, kinematic : No data available Viscosity, dynamic No data available

VOC content : 9 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO2 are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Welding.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

,		
Glycol Ether EB (111-76-2)		
LD50 oral rat	1300 mg/kg	
LD50 dermal rat	> 2000 mg/kg	
ATE CLP (oral)	1300.000 mg/kg body weight	
ATE CLP (dermal)	1100.000 mg/kg body weight	
ATE CLP (dust, mist)	1.500 mg/l/4h	
sodium hydroxide (1310-73-2)		
LD50 oral rat	>= ml/kg	

LD50 oral rat	>= ml/kg
2-aminoethanol, ethanolamine (141-43-5)	
LD50 oral rat	1720 mg/kg female
LD50 dermal rabbit	1000 mg/kg
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

 Date of issue: 8/17/2015
 Revision date: 05/18/2015
 Version: 1.0
 P GHS SDS
 Page 4 of 7

Safety Data Sheet



Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: 12 - 13

: Not classified Serious eye damage/irritation

pH: 12 - 13

Not classified Respiratory or skin sensitization Germ cell mutagenicity Not classified Carcinogenicity Not classified

Glycol Ether EB (111-76-2)

IARC group 3 - Not Classifiable

Not classified Reproductive toxicity Not classified Specific target organ toxicity (single exposure) Not classified. Specific target organ toxicity (repeated

exposure)

Glycol Ether EB (111-76-2)	
LOAEL (oral,rat,90 days)	69 mg/kg bodyweight/day Target organ: liver
NOAEL (dermal,rat/rabbit,90 days)	150 mg/kg bodyweight/day
A 1 1 1 1	A1

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause respiratory irritation. Symptoms/injuries after skin contact Caustic burns/corrosion of the skin. Symptoms/injuries after eye contact : Causes serious eye damage.

: Harmful if swallowed. Burns to the gastric/intestinal mucosa. Gastrointestinal complaints. Symptoms/injuries after ingestion

: Skin and eyes contact.;Inhalation Likely routes of exposure

SECTION 12: Ecological information

12.1. Toxicity

Glycol Ether EB (111-76-2)	
LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid

12.2. Persistence and degradability

sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the components available.

12.3. Bioaccumulative potential

sodium hydroxide (1310-73-2)	
Bioaccumulative potential	Does not contain bioaccumulative component(s).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container to

comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT: Not regulated for transport

: UN1950 Aerosols (non-flammable, (each not exceeding 1 L capacity)), 2.2 Transport document description

: UN1950 UN-No.(DOT) Proper Shipping Name (DOT) : Aerosols

non-flammable, (each not exceeding 1 L capacity)

Transport hazard class(es) (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Date of issue: 8/17/2015 P GHS SDS Page 5 of 7 Revision date: 05/18/2015 Version: 1.0

Safety Data Sheet



Hazard labels (DOT) : 2.2 - Non-flammable gas



: 306

: 150 kg

DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102)

DOT Packaging Exceptions (49 CFR

173.xxx)

DOT Quantity Limitations Passenger : 75 kg

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft

only (49 CFR 175.75)

DOT Vessel Stowage Location : A

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-butoxyethanol	CAS No 111-76-2	1.0 – 5.0
sodium hydroxide (1310-73-2)		
Not listed on SARA Section 313 (Specific toxic cl	nemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb	
propane (74-98-6)		
Not listed on SARA Section 313 (Specific toxic cl	nemical listings)	

California Proposition 65 - This product does not contain trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

7. C p	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 4	Flammable liquids Category 4

 Date of issue: 8/17/2015
 Revision date: 05/18/2015
 Version: 1.0
 P GHS SDS
 Page 6 of 7

Safety Data Sheet



Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H290	May be corrosive to metals
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure


NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury

unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 8/17/2015
 Revision date: 05/18/2015
 Version: 1.0
 P GHS SDS
 Page 7 of 7