## Safety Data Sheet



## SECTION 1: Product and company identification

Product name : Citra-Gel
Use of the substance/mixture : Aerosol
Product code : 838801

Company : Share Corporation P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Classification (GHS-US)

Flam. Aerosol 1 H222 Skin Irrit. 2 H315 Skin Sens. 1 H317 Asp. Tox. 1 H304

Full text of H-phrases: see section 16

#### 2.2. Label elements

## **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS07 G

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

May be fatal if swallowed and enters airways

Causes skin irritation

May cause an allergic skin reaction

Precautionary statements (GHS-US) : Keep away from heat, sparks, open flames, hot surfaces, Do not smoke. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Avoid breathing gas

Wash thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Wear protective gloves

If swallowed: Immediately call a doctor, a POISON CENTER

If on skin: Wash with plenty of water

Do NOT induce vomiting

If skin irritation or rash occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F Dispose of contents/container to comply with local/regional/national regulations

## 2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

## 3.2. Mixture

Date of issue: 8/17/2015 Revision date: 05/15/2015 Version: 1.0 P GHS SDS Page 1 of 7

## Safety Data Sheet



| Name                     | Product identifier  | %       | Classification (GHS-US)  |
|--------------------------|---------------------|---------|--|
| Citrus Terpenes          | (CAS No) 94266-47-4 | 60 - 80 | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Asp. Tox. 1, H304 |
| ODORLESS MINERAL SPIRITS | (CAS No) 64741-65-7 | 20 - 40 | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Asp. Tox. 1, H304    |
| propane                  | (CAS No) 74-98-6    | 10 - 20 | Flam. Gas 1, H220<br>Compressed gas, H280  |

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures general

: Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. show this sheet where possible. Keep watching the victim. Keep victim warm and rested. Wash contaminated clothing before reuse.

First-aid measures after inhalation

Move the affected person away from the contaminated area and into the fresh air. Artificial respiration and/or oxygen if necessary. IF INHALED: Do not apply mouth-to-mouth resuscitation. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve of other proper respiratory medical device. Immediately consult a doctor/medical service. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact

Remove/Take off immediately all contaminated clothing. Get immediate medical advice/attention.

Wash contaminated clothing before reuse.

First-aid measures after eye contact

Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion

Immediately call a poison center or doctor/physician. Rinse mouth. Do not induce vomiting without medical advice. Vomiting: prevent asphyxia/aspiration pneumonia. Ingestion of large quantities: immediately to hospital.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: None under normal use.

Symptoms/injuries after skin contact

Dermatitis. Skin rash/inflammation. Irritation. Red skin. May cause an allergic skin reaction. Causes

skin irritation.

Symptoms/injuries after eye contact

: Direct contact with the eyes is likely irritating.

Symptoms/injuries after ingestion

: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Symptoms may be delayed. Keep watching the victim.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media
Unsuitable extinguishing media

: Powder. Alcohol-resistant foam. Water fog. Carbon dioxide.

: Do not use a water jet since it may cause the fire to spread.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard

: Extremely flammable aerosol. May liberate toxic gases. Combustion produces irritating gases.

Explosion hazard

: Contains gas under pressure; may explode if heated.

Reactivity

: The product is non-reactive under normal conditions of use, storage and transport.

## 5.3. Advice for firefighters

Firefighting instructions

: In case of fire and/or explosion do not breathe fumes. Move containers away from the fire area if this can be done without risk. NEVER direct water jet on liquid. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Consider initial downwind evactuation for at least 500 meters (1/3 mile). Evacuate unnecessary personnel. Stay upwind/keep distance from source. Gas is denser than air. May accumulate in low areas e.g. close to the ground. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

Date of issue: 8/17/2015 Revision date: 05/15/2015 Version: 1.0 P GHS SDS Page 2 of 7

## Safety Data Sheet

# SHARE

## 6.1.1. For non-emergency personnel

Protective equipment

: Do not enter without an appropriate protective equipment. Do not breathe gas/vapor. DO NOT touch spilled material. Fully encapsulating, vapor protective clothing should be worn for spills and leaks

with no fil

Emergency procedures : Ventilate the area thoroughly, especially low lying areas (basements, work pits etc.). Advice local authorities if considered necessary.

#### 6.1.2. For emergency responders

No additional information available

## 6.2. Environmental precautions

Avoid discharge to the environment. Do not contaminate water with the product or its container. Do not allow to enter drains or water courses.

## 6.3. Methods and material for containment and cleaning up

For containment

Eliminate every possible source of ignition. NO open flames, NO sparks, and NO smoking. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Form with air vapors (heavier than air) who stay on the floor. Gas is denser than air. May accumulate in low areas e.g. close to the ground. This material is classified as a water pollutant under the Clean Water Act and should be prevented from

contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if safe to do so. Stop the leak. Turn leaking containers leak-side up to prevent the escape of liquid. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to disperse the vapors. Isolate area until gas has dispersed.

Methods for cleaning up

: Following product recovery, flush area with water. Clean thoroughly. Dispose as hazardous waste. Reference to other sections (13).

## 6.4. Reference to other sections

No additional information available

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Precautions for safe handling

: Vapors may form explosive mixture with air. Exclude sources of heat, sparks and open flame. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use only explosion-free electrical equipment with earth. Do not re-use empty containers. Obtain special instructions before use. Reduce/avoid exposure and/or contact. Do not breathe gas/vapor/aerosol. Avoid contact with skin, eyes and clothing. Avoid prolonged and repeated contact with skin. Use only outdoors or in a well-ventilated area. Wear positive pressure air supplied respirator if required by safe entry procedures. Wear recommended personal protective equipment.

Hygiene measures

Wash thoroughly after handling. Use good personal hygiene practices.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Store locked up. Refrigerate.

Incompatible products

: Refer to Section 10 on Incompatible Materials.

Incompatible materials

: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Storage area
Special rules on packaging

: Store in a cool area. Aerosol 3.

Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

| propane (74-98-6) |                      |          |
|-------------------|----------------------|----------|
| OSHA              | OSHA PEL (TWA) (ppm) | 1000 ppm |

### 8.2. Exposure controls

Appropriate engineering controls

: Provide sufficient air exchange and/or exhaust. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Avoid exposure, obtain special instructions before use.

Date of issue: 8/17/2015 Revision date: 05/15/2015 Version: 1.0 P GHS SDS Page 3 of 7

## Safety Data Sheet

Respiratory protection



Personal protective equipment

Use appropriate personal protective equipment when risk assessment indicates this is necessary.
 Gloves. Face shield. Protective clothing.







Hand protection : Avoid exposure, obtain special instructions before use.

Eye protection : Avoid exposure, obtain special instructions before use. Face shield. Avoid contact with eyes.

Skin and body protection : Avoid exposure, obtain special instructions before use. Avoid contact with skin. Wear chemical

protective equipment that is specifically recommended by the manufacturer. Use of an

impervious apron is recommended. It may provide little or no thermal protection.

: Avoid exposure, obtain special instructions before use. If permissible levels are exceeded use

NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazard protection : Use appropriate personal protective equipment when risk assessment indicates this is necessary.

Consumer exposure controls : When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Keep away from food

and drink. Use good personal hygiene practices. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash before reuse.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Aerosol.
Odor : fruity

Odor threshold : No data available pH : No data available Melting point : No data available Freezing point : No data available Boiling point : 182.21 °F Estimated

Flash point : -156 °F Propellant estimated

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available

Vapor pressure : 3.79 - 4.47 atm @ 70F estimated

Relative density No data available Relative vapor density at 20 °C : No data available Specific gravity / density 0.762 g/ml Estimated Solubility No data available Log Pow No data available Log Kow No data available Auto-ignition temperature : 509.38 Estimated Decomposition temperature : No data available Viscosity : No data available

Viscosity, kinematic : < 20 cSt

Viscosity, dynamic : No data available

#### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

## 10.2. Chemical stability

Risk of explosion. Risk of ignition. Unstable. The product is stable at normal handling- and storage conditions.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

Date of issue: 8/17/2015 Revision date: 05/15/2015 Version: 1.0 P GHS SDS Page 4 of 7

## Safety Data Sheet



## 10.4. Conditions to avoid

Heat. Open flame. Sparks. Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point. . Incompatible materials.

#### 10.5. Incompatible materials

Oxidizing agents.

## 10.6. Hazardous decomposition products

Thermal decomposition may produce: Nitrogen oxides. Phosphorous oxide.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| Aero-Gel                   |             |
|----------------------------|-------------|
| LD50 dermal rat            | 2781 mg/kg  |
| LC50 inhalation rat (mg/l) | 712 mg/l/4h |

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Not classified

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Not classified Carcinogenicity Not classified. Reproductive toxicity Not classified Specific target organ toxicity (single exposure) : Not classified. Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard Potential Adverse human health effects and

symptoms

: May be fatal if swallowed and enters airways.

Small amounts of liquid aspirated into the respiratory system during ingestion/vomiting may cause bronchopneumonia or pulmonary edema. Dermatitis. Allergic skin rash. skin irritation. Redness, pain.

: None under normal use.

Dermatitis. Skin rash/inflammation. Irritation. Red skin. May cause an allergic skin reaction. Symptoms/injuries after skin contact

Causes skin irritation.

Symptoms/injuries after eye contact

Symptoms/injuries after inhalation

Symptoms/injuries after ingestion

Direct contact with the eyes is likely irritating.

Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

No additional information available

## 12.2. Persistence and degradability

| ODORLESS MINERAL SPIRITS (64741-65-7) |   |
|---------------------------------------|---|
| Persistence and degradability         | No test data available. No (test)data on mobility of the substance available. |
| 12.3 Riogeoumulative notential        |   |

| ODORLESS MINERAL SPIRITS (64741-65-7) |                         |
|---------------------------------------|-------------------------|
| Bioaccumulative potential             | No test data available. |

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Waste treatment methods

Dispose of contents/container to comply with local/regional/national/international regulations. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. . Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. . Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this

product is considered a RCRA ignitable waste, D001. After recovery of solvent dispose of residue as hazardous waste.

Date of issue: 8/17/2015 Revision date: 05/15/2015 Version: 1.0 P GHS SDS Page 5 of 7

## Safety Data Sheet

SHARE

Additional information

: Containers, or internal liners coming from a container, having contained this product are also considered as hazardous wastes. This material and its container must be disposed of in a safe manner. Empty containers should be taken for recycle, recovery or waste in accordance with local regulation. Handle unclean empty containers as full ones.

## **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



Marine pollutant : Yes (IMDG only)



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

173.xxx)

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

: 75 kg

**DOT Quantity Limitations Cargo aircraft** 

only (49 CFR 175.75)

: 150 kg

DOT Vessel Stowage Location : A

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : This product may be elegible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
Proper Shipping Name (IMDG) : Aerosols

Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No.(IATA) : UN1950
Proper Shipping Name (IATA) : Aerosols

Class (IATA) : 2.1 - Gases : Flammable

## **SECTION 15: Regulatory information**

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylbenzene CAS No 100-41-4 0.01 - 0.1

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

Date of issue: 8/17/2015 Revision date: 05/15/2015 Version: 1.0 P GHS SDS Page 6 of 7

## Safety Data Sheet



## **SECTION 16: Other information**


## Full text of H-phrases:

| Asp. Tox. 1     | Aspiration hazard Category 1                                |
|-----------------|---|
| Compressed gas  | Gases under pressure Compressed gas                         |
| Flam. Aerosol 1 | Flammable aerosol Category 1                                |
| Flam. Gas 1     | Flammable gases Category 1                                  |
| Flam. Liq. 3    | Flammable liquids Category 3                                |
| Skin Irrit. 2   | Skin corrosion/irritation Category 2                        |
| Skin Sens. 1    | Skin sensitization Category 1                               |
| STOT SE 3       | Specific target organ toxicity (single exposure) Category 3 |
| H220            | Extremely flammable gas                                     |
| H222            | Extremely flammable aerosol                                 |
| H226            | Flammable liquid and vapor                                  |
| H280            | Contains gas under pressure; may explode if heated          |
| H304            | May be fatal if swallowed and enters airways                |
| H315            | Causes skin irritation                                      |
| H317            | May cause an allergic skin reaction                         |
| H336            | May cause drowsiness or dizziness                           |

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



#### Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 8/17/2015
 Revision date: 05/15/2015
 Version: 1.0
 P GHS SDS
 Page 7 of 7