

QuestSpecialty

MOLY TUFF

**Premium Multi-Purpose
Moly E.P. Grease**

MOLY TUFF

Premium Multi-Purpose Moly E.P. Grease

Premium Grasa Moly E.P. Multiusos

**Contains Moly Disulfide for
Added Performance**

Temperature Range of -20° to 500°F

All Weather Performance

**Extreme Pressure Additives
For High Loads**

Superb Rust & Corrosion Inhibitors

**Resists: Acids, Water, Salt Spray,
Dust & Dirt**

CAUTION/PRECAUCIÓN:
KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL CAUTIONS ON BACK PANEL
NO SE DEJE AL ALCANCE DE LOS NIÑOS
VEA PRECAUCIONES ADICIONALES EN EL PANEL TRASERO

NET CONTENTS: 14 OZ. (397 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
713.896.8188

A multi-use grease containing moly, high viscosity base oil and calcium sulfonate thickener system for hundreds of automotive, marine, industrial and agricultural applications. Extreme pressure additives provide resistance to shock. Forms a protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This water resistant lubricant will not wash out, and is resistant to corrosive salt water environments. Meets and exceeds the demanding automotive and industrial testing requirements of ASTM D 4950, earning it the GC-LB classification by the National Lubricating Grease Institute. This grease also meets Caterpillar CAT 5% moly requirements.

Recommended for the most severe applications in off-highway construction, mining equipment, earth moving machines, Caterpillar equipment, as well as other heavy duty construction and mining equipment moving at slow to medium speed.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

MODO DE EMPLEO: Inyecte grasa nueva hasta que la grasa vieja salga. Remueva la grasa vieja si es posible. Para conexiones de tipo bola, llene hasta que la grasa vieja salga. Limpie las áreas expuestas con desengrasante para remover la grasa vieja. Inyecte nueva grasa.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

PRECAUCIÓN: No se deje al alcance de los niños. Puede causar irritación a los ojos. El contacto prolongado puede causar irritación de la piel. Si es ingerido, puede causar náusea, vomito y diarrea. Si hay contacto con los ojos, enjuague con agua, vea a un médico si la sensación aceitosa persiste. Si hay contacto con la piel, lave con agua y jabón. Para la ingestión de más de 8 onzas contacte al médico.

CONTAINS (CAS#): Naphthenic Oil (64742-52-5), Graphite (7782-42-5), Molybdenum Disulfide (1317-33-5), Calcium Sulfonate Complex (N/A).

NLGI GRADE: 2

HMIS Ratings: Health - 1, Flammability - 1, Reactivity - 0, Personal - A.

Made in USA

600007249



ITEM L1 0200001-145G