

# MR. BLUE

## PREMIUM LITHIUM E.P. GREASE

### DESCRIPTION

**MR. BLUE** is a multi-use grease for hundreds of automotive, marine, industrial and agricultural applications. Does not dry out after use as some clay based greases do. Remains pumpable at low temperatures. Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out. Suitable for medium sized high speed bearings.

### APPLICATIONS

Excellent for use on ball bearings, roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, fifth wheels, wheel bearings, chassis.

### FEATURES & BENEFITS

- Resists thinning or hardening in medium sized high speed bearings
- Lithium grease with oxidation inhibitors & extreme pressure additives for a wide range of uses
- Protects surfaces against corrosion
- Operating range of -40°F to +350°F

### SPECIFICATIONS

**COLOR:** Blue  
**THICKENER:** Lithium Complex  
**NLGI GRADE:** 2  
**PENETRATION:** 265–295  
**DROPPING POINT:** 550°F – 600°F  
**TEMPERATURE RANGE:** 0°F – 350°F

**TIMKEN OK LOAD:** 60–70 lbs.  
**BASE OIL:** Petroleum Oil  
**VISCOSITY @ 40°C:** 224 CST  
**VISCOSITY @ 100°C:** 17.4 CST  
**FOUR BALL WELD LOAD:** 315 kg

### LABEL INFORMATION

#### MR. BLUE PREMIUM LITHIUM E.P. GREASE


A multi-use grease for hundreds of automotive, marine, industrial and agricultural applications. Does not dry out after use as some clay based greases do. Remains pumpable at low temperatures. Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out. Suitable for medium sized high speed bearings.

**DIRECTIONS FOR USE:** Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

**CAUTION:** Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

**CONTAINS (CAS#):** Naphthenic Oil (64742-52-5), Lithium 12-hydroxystearate (7620-77-1), Lithium stearate (4485-12-5), Elco 102 (68649-42-3), Lubrizol7065 OPC (N/A).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



### PACKAGING INFORMATION

Available in 14 oz. cartridges (10/case), 35 lb. pails, 120 and 400 lb. drums.