



RUST CONVERTER

HALTS EXISTING RUST AND PREVENTS FUTURE CORROSION WITH A DURABLE PROTECTIVE BARRIER

No sand blasting, grinding or scraping required.

DANGER:

EXTREMELY FLAMMABLE AEROSOL.
PRESSURIZED CONTAINER:
MAY BURST IF HEATED.

KEEP OUT OF REACH OF CHILDREN

See additional cautions on back panel.

NET WEIGHT: 13 oz. (369 g)

RUST CONVERTER surface conditioner and primer changes rust into a black, protective polymeric coating. It converts existing rust to an inert coating that seals out moisture to prevent future rust and corrosion. **RUST CONVERTER** provides an excellent primer coating for the application of quality oil-based paints. Surfaces protected with this primer and an oil-based paint resist the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces.



DANGER: Extremely flammable aerosol.

Pressurized container: may burst if heated. Causes serious eye irritation. Causes damage to organs. May cause respiratory irritation, drowsiness, or dizziness. May cause damage to organs through prolonged or repeated exposure. spray. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn even after use. Do not eat, drink, or smoke when using this product. Do not breathe mist, vapor, or spray. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, and eye protection. Use only outdoors or in a well-ventilated area. Get medical advice/attention if you feel unwell.

RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF EXPOSED OR CONCERNED: Call a POISON CENTER or doctor/physician.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

STORAGE:

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

DISPOSAL:

Dispose of contents and container in accordance with local, state and national regulations.

INGREDIENTS/CAS#:

Acetone (67-64-1), Butane (106-97-8), Isopropanol (67-63-0), Propane (74-98-6), 2-Butoxyethanol (111-76-2).

NFPA® RATINGS:

Health: *3; Flammability: 3; Reactivity: 0

DIRECTIONS:

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: SHAKE WELL BEFORE USING. Do not apply if the surface temperature is below 50°F or above 90°F. Hold can 8-12 inches from surface and spray a thin, even coat onto the surface.

DRYING TIME: The resulting coat will dry to a smooth, black finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces, while protecting it from rain and dew. Allow 48 hours of cure time before the application of the finished paint coat.

For a long-lasting protection of treated surfaces, the cured **RUST CONVERTER** coating should be sealed with two coats of a high-quality oil-based paint. No other primer is required.

Sold by:

8347.062326

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com